United States Environmental Protection

Agency

Office of Air Quality Planning and Standards Information Transfer and Program Integration Division

Information Management Group Research Triangle Park, NC 27711

⇔EPA AQS Data Coding Manual (AQ2)

VERSION 1.4

Date Revised: 12/23/03

Note to our users:
If you were familiar with the "old" mainframe system, you should recognize almost all of the old fields and terminology in the "new" system, because the "new" system still addresses the "old" monitoring program data needs.
The Appendices attached to this manual contain codes and descriptions from the various AQS tables. Over time, the list of code values may change, so we will routinely update this manual. Besides using these appendices, the current list of codes and descriptions can also be obtained by using drop-down lists in the AQS Client, or by using the powerful Oracle Discoverer tool.
We plan on making improvements to this manual in the future. And we hope this manual helps make the job of data entry a little more straightforward for you. If you have suggestions or see corrections that should be made, please let us know. Thank you for your cooperation, and your work to protect our Nation's air quality.
The Information Management Group, OAQPS,USEPA

AQS DATA CODING MANUAL

(AQ2)

VERSION 1.4

12/23/03

U.S. ENVIRONMENTAL PROTECTION AGENCY
OFFICE OF AIR QUALITY PLANNING AND STANDARDS
INFORMATION TRANSFER AND PROGRAM INTEGRATION DIVISION
INFORMATION MANAGEMENT GROUP
RESEARCH TRIANGLE PARK, NC 27711

Table of Contents

1.0 In	ntroduction	1-1
2.0 O	Overview of Data Coding and Validation	2-1
2.1 A	AQS Transactions	2-1
2.2	General Coding Instructions	2-1
2.2.1	Codes	2-1
2.2.2	Dates	2-2
2.2.3	Numeric Values	2-2
2.2.4	Alphanumeric Values	2-2
2.2.5	Deletion of Non-Key Values Using Batch Transactions	2-2
2.2.6	Transaction Dependencies	2-2
2.2.7	Mandatory Fields	
3.0	Common Fields	3-1
3.0.1	Transaction Type	3-1
3.0.2	Action Code	3-1
3.0.3	State Code	3-2
3.0.4	County Code	3-3
3.0.5	Site ID	
4.0 Si	ite Transactions (AA, AB, AC)	4-1
41 D	Dagia Sita Information - Tuonga ation Type A A	4.2
4.1 b 4.1.1	Basic Site Information - Transaction Type AA Transaction Type	
4.1.1	Action Code	
4.1.2	State Code	
4.1.3	County Code	
4.1.4	Site ID	
4.1.6	Latitude	
4.1.7	Longitude	
4.1.7	UTM Zone	
4.1.9		
	UTM Northing	
4.1.11		
	2 LDP Horizontal Datum	
	3 LDP Source Scale	
	LDP Measurement Accuracy Value	
	5 LDP Vertical Measure	
	5 Time Zone	
	Support Agency	
	Street Address	
4.1.19	9 City Code	4-12

4.1.20	Urban Area Code	4-12
4.1.21	ACQR	4-13
4.1.22	Land Use	4-13
4.1.23	Location Setting	4-13
4.1.24	Date Site Established	4-14
4.1.25	Date Site Terminated	4-14
4.1.26	ZIP Code	4-14
4.1.27	Congressional District	4-15
4.1.28	Block	
4.1.29	Block Group	4-15
4.1.30	Census Tract	4-15
4.1.31	Class I Area	4-16
4.1.32	Local Region	4-16
4.1.33	Local Site Name	4-16
4.1.34	HQ Evaluation Date	4-17
4.1.35	Regional Evaluation Date	4-17
4.1.36	Compass Sector	4-17
4.1.37	Distance to City	4-18
4.1.38	Type Meteorological Site	4-18
4.1.39	Meteorological Site ID	
4.1.40	Distance to Meteorological Site	4-19
4.1.41	Direction to Meteorological Site	4-19
4.1.42	State or Local ID	4-19
4.1.43	LDP Vertical Method	
4.1.44	LDP Vertical Datum	4-20
4.1.45	LDP Vertical Accuracy Value	4-21
4.2	Site Street Information - Transaction Type AB	4-22
4.2.1	Transaction Type	4-22
4.2.2	Action Code	4-22
4.2.3	State Code	4-22
4.2.4	County Code	4-23
4.2.5	Site ID	4-23
4.2.6	Tangent Street Number	4-24
4.2.7	Street Name	4-24
4.2.8	Type Road	4-24
4.2.9	Traffic Count	4-25
4.2.10	Year of Traffic Count	4-25
4.2.11	Direction to Street	4-25
4.2.12	Source of Traffic Count	4-25
4.3 S	Site Open Path Information - Transaction Type AC	4-27
4.3.1	Transaction Type	4-27
4.3.2	Action Code	4-27
4.3.3	State Code	4-27
4.3.4	County Code	4-28

4.3.5	Site ID	4-28
4.3.6	Open Path Number	4-29
4.3.7	Direction to Transmitter	4-29
4.3.8	Beam Length	4-29
4.3.9	Height of Transmitter	
4.3.10	<u> </u>	
4.3.11		
4.3.12	<u> </u>	
4.3.13		
4.4 \$	Site Comments (Online Update Only)	4-32
5.0 N	Monitor Transactions (MA - MK)	5-1
5.1 B	Basic Monitor Information - Transaction Type MA	5-5
5.1.1	Transaction Type	5-5
5.1.2	Action Code	5-5
5.1.3	State Code	5-5
5.1.4	County Code	5-6
5.1.5	Site ID	5-6
5.1.6	Parameter	5-7
5.1.7	POC (Parameter Occurrence Code)	5-7
5.1.8	Project Class	5-8
5.1.9	Dominant Source	5-8
5.1.10	Measurement Scale	5-8
5.1.11	Open Path Number	5-9
5.1.12	Probe Location Code	5-9
5.1.13	Probe Height	5-9
5.1.14	Horizontal Distance	5-9
5.1.15	Vertical Distance	5-10
5.1.16	Surrogate Flag Indicator	5-10
5.1.17	Unrestricted Air Flow Indicator	5-10
5.1.18	Sample Residence Time	5-11
5.1.19	Worst Site Type	5-11
5.1.20	Applicable NAAQS Indicator	5-12
5.1.21	Spatial Average Indicator	5-12
5.1.22	Schedule Exemption Indicator	5-13
5.1.23	Community Monitoring Zone	5-13
5.1.24	Pollutant Area Code 1, 2, 3, 4, or 5	5-13
	Monitor Sampling Periods - Transaction Type MB	
5.2.1	Transaction Type	
5.2.2	Action Code	
5.2.3	State Code	
5.2.4	County Code	
5.2.5	Site ID	5-16

5.2.6	Parameter	5-17
5.2.7	POC (Parameter Occurrence Code)	
5.2.8	Date Sampling Began	
5.2.9	Date Sampling Ended	
5.3	Monitor Type Information - Transaction Type MC	5-19
5.3.1	Transaction Type	
5.3.2	Action Code	
5.3.3	State Code	
5.3.4	County Code	
5.3.5	Site ID.	
5.3.6	Parameter	
5.3.7	POC (Parameter Occurrence Code)	
5.3.8	Monitor Type	
5.3.9	Monitor Type Begin Date	
5.3.10		
	71	
5.4	Monitor Agency Role - Transaction Type MD	5-24
5.4.1	Transaction Type	5-24
5.4.2	Action Code	5-24
5.4.3	State Code	5-24
5.4.4	County Code	5-25
5.4.5	Site ID	5-25
5.4.6	Parameter	5-26
5.4.7	POC (Parameter Occurrence Code)	5-26
5.4.8	Agency Role Name	
5.4.9	Agency Code	5-27
5.4.10	e ;	
5.4.11	\mathcal{E}	
	Monitoring Objective Information - Transaction Type ME	5-29
5.5.1	Transaction Type	5-29
5.5.2	Action Code	5-29
5.5.3	State Code	5-29
5.5.4	County Code	5-30
5.5.5	Site ID	5-30
5.5.6	Parameter	5-31
5.5.7	POC (Parameter Occurrence Code)	5-31
5.5.8	Monitor Objective	
5.5.9	Urban Area Represented	
5.5.10		
5.5.11	1	
	· · · · · · · · · · · · · · · · · · ·	
5.6	Monitoring Sampling Schedule - Transaction Type MF	
5.6.1	Transaction Type	
5.6.2	Action Code	5-34

5.6.3	State Code	5-34
5.6.4	County Code	5-35
5.6.5	Site ID.	5-35
5.6.6	Parameter	5-36
5.6.7	POC (Parameter Occurrence Code)	5-36
5.6.8	RCF (Required Collection Frequency) Code	
5.6.9	RCF Begin Date	
5.6.10	RCF End Date.	
5.6.11	Collection Frequency - January to December (12 instances)	5-38
5.7 N	Monitor Street Description - Transaction Type MG	5-39
5.7.1	Transaction Type	
5.7.2	Action Code	5-39
5.7.3	State Code	5-39
5.7.4	County Code	5-40
5.7.5	Site ID.	
5.7.6	Parameter	5-41
5.7.7	POC (Parameter Occurrence Code)	5-41
5.7.8	Tangent Street Number	
5.7.9	Distance from Monitor	5-42
5.8 N	Monitor Obstruction Information - Transaction Type MH	5-43
5.8.1	Transaction Type	
5.8.2	Action Code	
5.8.3	State Code	5-43
5.8.4	County Code	5-44
5.8.5	Site ID.	5-44
5.8.6	Parameter	5-45
5.8.7	POC (Parameter Occurrence Code)	5-45
5.8.8	Type Obstruction	
5.8.9	Director from Monitor	5-46
5.8.10	Distance to Monitor	5-46
5.8.11	Height of Obstruction	5-47
5.9 N	Monitor Regulatory Compliance - Transaction Type MI	5-48
5.9.1	Transaction Type	
5.9.2	Action Code	5-48
5.9.3	State Code	5-48
5.9.4	County Code	5-49
5.9.5	Site ID.	5-49
5.9.6	Parameter	5-50
5.9.7	POC (Parameter Occurrence Code)	5-50
5.9.8	Monitor Regulation Code	5-51
5.9.9	Compliance Indicator	5-51
5 9 10	Compliance Date	5-51

5.10 N	Monitor Collocation Period - Transaction Type MJ	5-53
5.10.1	Transaction Type	5-53
5.10.2	Action Code	5-53
5.10.3	State Code	5-53
5.10.4	County Code	5-54
5.10.5	Site ID	5-54
5.10.6	Parameter	5-55
5.10.7	POC (Parameter Occurrence Code)	
5.10.8	Collocation Begin Date	5-56
5.10.9	Collocation End Date	
5.10.10	Distance from Primary Monitor	5-57
5.10.11	Primary Monitor Indicator	5-57
5.11 I	Monitor Protocol - Transaction Type MK	5-58
5.11.1	Transaction Type	
5.11.2	Action Code	5-58
5.11.3	State Code	5-58
5.11.4	County Code	5-59
5.11.5	Site ID	5-59
5.11.6	Parameter	5-60
5.11.7	POC (Parameter Occurrence Code)	5-60
5.11.8	Alternate MP ID	5-61
5.11.9	Sample Duration	5-61
5.11.10	Unit	5-61
5.11.11	Method	5-62
5.11.12	Collection Frequency	5-62
5.11.13	Composite Type	5-62
5.11.14	Alternate Method Detectable Limit	5-63
5.12 I	Monitor Comments (Online Input Only)	5-64
6.0 R	aw Data Transactions (RC, RD)	6-1
6.1 Co	omposite Raw Data - Transaction Type RC	6.3
	Transaction Type	
	Action Code	
	State Code	
	County Code	
	Site ID	
	Parameter.	
	POC (Parameter Occurrence Code)	
	Unit	
	Method	
6.1.10	Year	
6.1.11	Period	
	Number of Samples.	
	OI COLLIDIA COLL	

6.1.13	Composite Type	6-7
6.1.14		
6.1.15	Alternate MP ID	6-9
6.1.16	Qualifier 1-10.	6-9
6.1.17		
6.1.18		
	· · · · · · · · · · · · · · · ·	
6.2	Hourly, Daily, and Sub-Hourly Raw Data - Transaction Type RD	6-11
6.2.1	Transaction Type	6-11
6.2.2	Action Code	6-11
6.2.3	State Code	6-11
6.2.4	County Code	6-12
6.2.5	Site ID	6-12
6.2.6	Parameter	6-13
6.2.7	POC (Parameter Occurrence Code)	6-13
6.2.8	Sample Duration	6-14
6.2.9	Unit	6-14
6.2.10	Method	6-14
6.2.11	Date	6-15
6.2.12	Start Time	6-15
6.2.13	Sample Value	6-15
6.2.14	Null Data Code	6-18
6.2.15	Collection Frequency	6-18
6.2.16	Alternate MP ID	6-18
6.2.17	V Qualifier 1-10	6-19
6.2.18	Method Detectable Limit	6-19
6.2.19	Uncertainty	6-20
	·	
6.3	Statistical Tests	6-21
6.3.1	Pattern Tests	6-21
6.3.2	Gap Test	6-24
6.3.3	Patterns and Gap Failure Report	6-24
6.3.4	Shewhart Test	6-25
7.0	Accuracy/Precision Transactions (RA, RP)	7-1
	Accuracy Data - Transaction Type RA	
7.1.1	Transaction Type	
7.1.2	Action Code	
7.1.3	State Code	
7.1.4	County Code	
7.1.5	Site ID	
7.1.6	Parameter	
7.1.7	POC (Parameter Occurrence Code)	
7.1.8	Accuracy Audit ID Number	
7.1.9	Sample Duration	7-5

7.1.1	0 Unit	7-6
7.1.1	1 Method	7-6
7.1.1	2 Year Represented	7-6
7.1.1	3 Quarter Represented	7-6
7.1.1	4 Date	7-7
7.1.1	5 Type Audit	7-7
7.1.1	6 Local Primary Standard	7-7
7.1.1	7 Audit Class	7-8
7.1.1	8 Accuracy Type	7-8
7.1.1	9 Audit Sample ID	7-8
7.1.2	20 Expiration Date	7-9
7.1.2	21 Audit Scheduled	7-9
7.1.2	22 Level 1-4 Actual Value	7-9
7.1.2	23 Level 1-1 Indicated Value	7-11
7.1.2	24 Other Level Actual Value	7-12
7.1.2	25 Other Level Indicated Value	7-13
7.1.2	26 Zero Span	7-13
7.2	Precision Data - Transaction Type RP	7-14
7.2.1	Transaction Type	7-14
7.2.2	2 Action Code	7-15
7.2.3	State Code	7-15
7.2.4	County Code	7-15
7.2.5		
7.2.6	S Parameter	7-16
7.2.7	POC (Parameter Occurrence Code)	7-17
7.2.8	Precision ID	7-17
7.2.9	Sample Duration	7-18
7.2.1	0 Unit	7-18
7.2.1		
7.2.1	2 Date	7-19
7.2.1	3 Actual Value	7-19
7.2.1		
7.2.1	5 Indicated Value	7-21
7.2.1	6 Collocated POC ID	7-22
7.2.1	7 Precision Sample ID	7-22
7.2.1	8 Agency Performing Audit	7-23
8.0	Annual Summary Data - Transaction Type RS	
8.1	Transaction Type	
8.2	Action Code	
8.3	State Code	8-2
8.4	County Code	
8.5	Site ID	
	Parameter	
8.7	POC (Parameter Occurrence Code)	8-3

8.8	Sample Duration8-4						
8.9	Unit8-4						
8.10	0 Method8						
8.11	Year8-						
8.12							
8.13	Count of Observations	8-5					
8.14	Number of Exceptional Events	8-6					
8.15	Highest Sample Value	8-6					
8.16	Date of Highest Sample Value	8-6					
8.17	Time of Highest Sample Value	8-7					
8.18	Second Highest Sample Value	8-7					
8.19							
8.20							
8.21	Third Highest Sample Value	8-8					
8.22	Fourth Highest Sample Value	8-8					
8.23	Fifth Highest Sample Value	8-8					
8.24	Lowest Sample Value	8-9					
8.25	Arithmetic Mean	8-9					
8.26	Arithmetic Standard Deviation	8-9					
8.27	Geometric Mean	8-9					
8.28							
8.29							
8.30							
8.31							
8.32	75 th Percentile	8-11					
8.33	90 th Percentile	8-11					
8.34	95 th Percentile	8-11					
8.35	98th Percentile	8-12					
8.36	99th Percentile	8-12					
8.37	Percent of Observations.	8-12					
8.38	Number Less Than Minimum Detectable Value	8-12					
	Tables						
	e 6-1 Conversion Factors for the Pattern and Gap Tests						
rabl	e 6-2 Threshold Values for the Pattern Tests	6-23					

1.0 INTRODUCTION

This manual explains how to use the Air Quality System (AQS). AQS is a computer-based system for handling the storage and retrieval of information pertaining to airborne pollutants. It is administered by the U.S. Environmental Protection Agency, Office of Air Quality Planning and Standards (OAQPS) in Research Triangle Park, North Carolina.

Volume AQ1 contains the AQS data dictionary. This volume, AQ2, describes coding of air quality (AQ) data transactions.

This volume describes the various transactions used to create, update, or delete data in the Air Quality System. It is intended for those individuals who are responsible for maintaining the air quality data for their organizations.

The remainder of this volume is organized as follows:

Section 2 - Overview of Data Coding and Validation

Section 3 - Common Fields

Section 4 - Site Transactions (AA, AB, AC)

Section 5 - Monitor Transactions (MA, MB, MC, MD, ME, MF, MG, MH, MI, MJ, MK)

Section 6 - Raw Data Transactions (RC, RD)

Section 7 - Precision/Accuracy Transactions (RA, RP)

Section 8 - Annual Summary Data (RS)

2.0 OVERVIEW OF DATA CODING AND VALIDATION

The Air Quality System contains data from state and local agencies, tribes, and federal organizations. It includes descriptions of air monitoring sites and monitoring equipment, measured concentrations of air pollutants and related parameters, and calculated summary and statistical information. This is called air quality (AQ) data throughout the rest of this volume.

Reporting agencies submit AQ data as formatted transactions by first loading the transaction file(s) to EPA's Central Data Exchange (CDX). Files loaded to CDX are then available to AQS for the batch load process. (Note that online data entry via data screens is also available, in addition to using the batch process.) The user then employs AQS software to process the data through five steps of batch loading, starting with file loading to AQS and ending with posting the data to the database. Internet Explorer (a Web browser) is used to access both CDX and AQS applications.

2.1 AQS TRANSACTIONS

Nineteen types of transactions are used to provide data and control information for updating the AQS database. Detailed instructions for coding individual transactions are presented in Chapters 3 through 7.

Appendix L presents the transaction formats. For each transaction, the fields are listed, along with required fields.

Appendix QQ shows which transactions are needed at a minimum to create site and monitor data. The required transactions, depending on type of data, are indicated.

2.2 GENERAL CODING INSTRUCTIONS

Four general types of values are used to code air quality transactions: codes, dates, numeric data, and alphanumeric data.

2.2.1 Codes

Codes must be entered on transactions exactly as they are stored in the AQS tables. For example, a county code is three digits, and you must code all three digits of the code, including any leading zeros. The instructions for fields that take a code value include the term "code" in the list of field attributes. Code values are included in the Appendices of this volume. The larger tables of code values are also available as drop-down lists in the AQS Client software.

Many alphanumeric fields have a restricted list of values stored in the AQS tables; other alphanumeric fields are text fields in which any entries are valid. All of the values (codes) stored in the AQS code tables (formerly GeoCommon tables) are capitalized. Therefore, when supplying code values on batch transactions, capitalization is required for successful processing.

2.2.2 Dates

Dates are entered in YYYY, or YYYYMMDD format. YYYY is year, MM is month number, DD is day number. The instructions for fields that take a date value include the term "date" in the list of field attributes.

2.2.3 Numeric Values

The instructions for fields that take a numeric value include the term "numeric" in the list of field attributes. The convention for number of digits and decimal places in this manual is: total number of digits, followed by a comma, followed by the number of decimal places. For example, 10,5 is a ten-digit number including five decimal places (nnnnn.nnnn).

2.2.4 Alphanumeric Values

The instructions for these fields include the term "character" in the list of field attributes. The length of allowable text is specified for each field. Many alphanumeric fields are validated against reference tables in AQS. For these fields, the values entered must match exactly the values on the appropriate reference tables.

2.2.5 Deletion of Non-Key Field Values Using Batch Transactions

The deletion of non-key field values (without deleting the entire record) is no longer supported in the batch transaction mode. The use of asterisks in field values to signify field deletion is no longer supported. The AQS client now has an online maintain function which will allow interactive deletion of a single field.

2.2.6 Transaction Dependencies

More than one transaction type may be required to insert (add) new data to the database. The transactions required will vary according to the type of data being inserted. Sometimes the value of a field may require an additional transaction. The transaction dependencies for the transactions needed to insert sites and monitors are shown in Appendix QQ.

2.2.7 Mandatory Fields

Certain fields are mandatory (required), and they must have a value on the transaction. Some fields are always mandatory; other fields are mandatory only under certain conditions. For example, action code is always mandatory; it must be coded on every transaction. The coding instructions in subsequent chapters identify fields as Mandatory or Optional, and specify the conditions when a value is mandatory on the transaction. Also, the batch transaction formats contain notes showing

various dependencies and required fields.

The old transaction formats are still supported for raw data, with the exception of non-key field deletions using asterisks. The old transaction formats are column-specified and no delimiters are used. Old transaction formats are all fixed at 80 characters in length.

The new transaction formats make use of field delimiters, rather than column position, to determine which field is to be processed. The delimiter character is the vertical bar " | ". Transactions, therefore, always start with the two-character transaction type, followed by the delimiter character, followed by the one-character action code (I, U, or D), followed by the delimiter character, followed by the next field (state), etc. The transactions must have the proper number of delimiters. If non-key fields are to be ignored, then the delimiters are included directly following the last delimiter (no spaces). For two transaction types (RD and RC), missing delimiters at the end of the transaction record are treated as null fields, i.e. the missing delimiters are assumed to be there by the batch update software. Again, this only applies to transaction types RD and RC.

3.0 COMMON FIELDS

The 19 AQS transaction formats contain certain fields in common. These common fields are described in this chapter. The unique fields for each transaction are described in the following chapters.

3.0.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

Valid transaction types are:

AA, AB, AC for site transactions

MA, MB, MC, MD, ME, MF, MG, MH, MI, MJ, MK for monitor

transactions

RC, RD for raw data transactions (composite and hourly, daily, sub-hourly)

RA, RP for accuracy and precision transactions

RS for annual summary data

3.0.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

Transaction Type	Action Code	Database Processing
44.40	I	Insert a new site into the Site Table.
AA-AC	U	Change or delete one or more column values within a Site Table row.
AA	D	Delete a site from the Site Table (you must also delete all of its monitors).
	I	Insert a new monitor into the Site Table.
MA-MK	U	Change or delete one or more column values within a Monitors Table row in the Site Table.
MA	D	Delete a monitor from the Site Table (you must delete all its raw data first).
	I	Insert new values into the Raw Data Table.
RC, RD	U	Change or delete existing values in the Raw Data Table.
	D	Delete existing values from the Raw Data Table.
	I	Insert precision data for collected samples.
RP	U	Change existing precision value(s).
	D	Delete existing precision values for a specified time interval.
	I	Insert a new accuracy value in the Accuracy Data Table for a specified time interval.
RA	U	Change an existing accuracy value in the Accuracy Data Table.
	D	Delete existing accuracy values for a specified time interval from the Accuracy Data Table.
	I	Insert summary data for a pollutant for a year (when no corresponding raw data exists.
RS	U	Change existing summary values.
	D	Delete existing summary values.

3.0.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-digit code Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

3.0.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table

3.0.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

4.0 SITE TRANSACTIONS (AA, AB, AC)

This set of three transactions is used to update Site information.

Type AA, Basic Site Information, performs data manipulation on the Sites and Agency Roles Tables, and contains site information in the following fields:

Transaction Type Date Site Established Action Code Date Site Terminated

State Code ZIP Code

County Code Congressional District

Site ID Block

Latitude Block Group
Longitude Census Tract
UTM Zone Class I Area
UTM Easting Local Region
UTM Northing Local Site Name
LDP Method of Collection HQ Evaluation Date
LDP Horizontal Datum Regional Evaluation Date

LDP Source Scale Compass Sector
LDP Measurement Accuracy Value Distance to City

LDP Vertical Measure Type Meteorological Site
Time Zone Meteorological Site ID

Support Agency Distance to Meteorological Site Street Address Direction to Meteorological Site

City Code State or Local ID
Urban Area Code LDP Vertical Method
AOCR LDP Vertical Datum

Land Use LDP Vertical Accuracy Value

Location Setting

Type AB, Site Street Information, performs data manipulation on the Tangent Roads Table, and contains site information in the following fields:

Transaction Type Street Name
Action Code Type Road
State Code Traffic Count

County Code Year of Traffic Count
Site ID Direction to Street
Tangent Street Number Source of Traffic Count

Type AC, Site Open Path Information, performs data manipulation on the Open Paths Table, and contains site information in the following fields:

Transaction Type State Code
Action Code County Code

Site ID Open Path Number Direction to Transmitter Beam Length Height of Transmitter Height of Receiver Minimum Height Maximum Height Land Use Under Path

Insert transactions (i.e., transactions with action code I) are used to create a new site in the site file. When creating a new site, only one type AA is allowed, while multiple AB and AC transactions can be entered. Each AB transaction supplies information for one street surrounding a site. Each AC transaction supplies information for one open path monitor at a site.

Update transactions (i.e., transactions with action code U) are used to change the contents of site-specific fields in the Site Table. Blank fields on an update transaction are ignored; they do not affect the Site Table. The values coded on an update transaction replace the values of the corresponding columns in the Site Table. If no value existed previously, the value from the transaction is inserted into the row of the Site Table.

Delete transactions (i.e., transactions with action code D) are used to remove sites from the Site Table. Use a delete action code D on Type AA to remove a site from the Site Table. A site may not be deleted if any monitors for that site remain in the Site Table. You must delete the site and its last monitor(s) at the same time.

Old transactions are converted for raw data transactions only, not for site, monitor, or summary.

See the Transaction Requirements Table in the Appendices to see which data input transactions are required to create sites. Also, the data input transaction formats are included as an appendix.

4.1 BASIC SITE INFORMATION - TRANSACTION TYPE AA

The fields described in this section are validated for insert (I) and update (U) transactions, but not for delete (D) transactions. The state, county, and site fields are always validated, as described in Section 3 above. For an update transaction, fields other than state code, county code, and site ID must be not be blank.

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors.

See the data input transaction formats in the Appendices for a list of required fields on each transaction format.

4.1.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

4.1.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

4.1.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

4.1.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

4.1.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether

a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

4.1.6 Latitude

Description: The monitoring site's angular distance north or south of the equator measured

in decimal degrees. The associated sign specifies the direction of measurement, a positive number indicating north and negative indicating south. EPA Locational Data Policy (LDP) requires that coordinates be provided for all sites. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website

(http://www.epa.gov/edr/).

Attributes: Numeric

Optional

Coding Instructions: A site's coordinates may be given either as latitude/longitude or universal

transverse Mercator (UTM) coordinates, but not both. (When latitude is provided on the transaction, longitude must also be provided, but UTM values must not be provided.) When latitude and longitude are provided on the transaction, the UTM coordinates are system-generated during the load step for the Sites Table (for insert and update action codes). Therefore, all

Sites Table rows contain both latitude/longitude and UTM coordinates.

To insert or update, place a latitude value, in decimal degrees, in the sixth delimited field. For a coordinate above the equator, enter the value as a positive number. For a coordinate below the equator, enter the value as a

negative number.

4.1.7 Longitude

Description: The monitoring site's angular distance east or west of the prime meridian at

Greenwich, measured in decimal degrees. The associated sign specifies the direction of measurement, a positive number indicating east and negative indicating west. EPA Locational Data Policy requires that coordinates be provided for all sites. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR)

Website (http://www.epa.gov/edr/).

Attributes: Numeric

Optional

Coding Instructions: A site's coordinates may be given either as latitude/longitude or UTM

coordinates, but not both. (When longitude is provided on the transaction, latitude must also be provided, but UTM values must not be provided.) When latitude and longitude are provided on the transaction, the UTM coordinates are system-generated during the load step for the Sites Table (for insert and update action codes). Therefore, all Sites Table rows contain both

latitude/longitude and UTM coordinates.

To insert or update, place a longitude value, in decimal degrees, in the seventh delimited field. For a coordinate west of the prime meridian, enter the value as a positive number. For a coordinate east of the prime meridian,

enter the value as a negative number.

4.1.8 UTM Zone

Description: The zone of the universal transverse Mercator (UTM) system in which a site

is located. EPA Locational Data Policy requires that coordinates be provided for all sites. AQS will convert the UTM coordinates to latitude/longitude, and store both UTM and latitude/longitude. More information regarding EPA's data standards and policies may be found on EPA's Environmental

Data Registry (EDR) Website (http://www.epa.gov/edr/).

Attributes: Numeric

12 digits (nnnnnnnnnnn)

Optional

Coding Instructions: A site's coordinates may be given either as latitude/longitude or UTM

coordinates, but not both. (When UTM zone is provided on the transaction, UTM easting and UTM northing must also be provided, but latitude/longitude values must not be provided.) When UTM coordinates are provided on the transaction, latitude and longitude are system-generated for

the Sites Table during the load step (for insert and update action codes). Therefore, all Sites Table rows contain both latitude/longitude and UTM coordinates.

To insert or update, place a UTM zone value in the eighth delimited field.

4.1.9 UTM Easting

Description: The easting UTM coordinate, expressed in meters (i.e., the horizontal

distance from the reference edge of the UTM zone) for the site. EPA Locational Data Policy requires that coordinates be provided for all sites. AQS will convert the UTM coordinates to latitude/longitude, and store both UTM and latitude/longitude. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry

(EDR) Website (http://www.epa.gov/edr/).

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Optional

Coding Instructions: A site's coordinates may be given either as latitude/longitude or UTM

coordinates, but not both. (When UTM easting is provided on the transaction, UTM zone and UTM northing must also be provided, but latitude/longitude values must not be provided.) When UTM coordinates are provided on the transaction, latitude and longitude are system-generated for the Sites Table during the load step (for insert and update action codes). Therefore, all Sites Table rows contain both latitude/longitude and UTM

coordinates.

To insert or update, place a UTM easting value in the ninth delimited field.

4.1.10 UTM Northing

Description: The northing UTM coordinate expressed in meters (i.e., for the Northern

hemisphere, the vertical distance from the equator; for the Southern hemisphere, 10,000,000 minus the vertical distance from the equator) for the site. EPA Locational Data Policy requires that coordinates be provided for all sites. AQS will convert the UTM coordinates to latitude/longitude, and store both UTM and latitude/longitude. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data

Registry (EDR) Website (http://www.epa.gov/edr/).

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Optional

Coding Instructions:

A site's coordinates may be given either as latitude/longitude or UTM coordinates, but not both. (When UTM northing is provided on the transaction, UTM zone and UTM easting must also be provided, but latitude/longitude values must not be provided.) When UTM coordinates are provided on the transaction, latitude and longitude are system-generated for the Sites Table during the load step (for insert and update action codes). Therefore, all Sites Table rows contain both latitude/longitude and UTM coordinates.

To insert or update, place a UTM northing value in the tenth delimited field.

4.1.11 LDP Method of Collection

Description: Method used to determine the latitude/longitude or UTM coordinates.

Required by EPA Locational Data Policy (LDP). More information regarding EPA's data standards and policies may be found on EPA's Environmental

Data Registry (EDR) Website (http://www.epa.gov/edr/).

Attributes: Alphanumeric

3-digit code (nnn)

Mandatory

Coding Instructions: Place a valid LDP method of collection code in the eleventh delimited field.

A code is valid if it is in the LDP Collection Methods Table. View code descriptions in the Appendices, or via Discoverer, and choose the appropriate code. Examples of code values for this data element are given below.

LDP Method Of Collection Codes as of September 11, 2003 are:

remod of concentration codes as of septemeer 11, 2003 are.
Description
ADDRESS MATCHING-HOUSE NUMBER
ADDRESS MATCHING-BLOCK FACE
ADDRESS MATCHING-STREET CENTERLINE
ADDRESS MATCHING-NEAREST INTERSECTION
ADDRESS MATCHING-PRIMARY NAME
ADDRESS MATCHING-DIGITIZED
ADDRESS MATCHING-OTHER
CENSUS BLOCK-1990-CENTROID
CENSUS BLOCK/GROUP-1990-CENTROID
CENSUS BLOCK/TRACT-1990-CENTROID
CENSUS-OTHER
GPS CARRIER PHASE STATIC RELATIVE POSITION
GPS CARRIER PHASE KINEMATIC RELATIVE POSITION
GPS CODE (PSEUDO RANGE) DIFFERENTIAL

- 015 GPS CODE (PSEUDO RANGE) PRECISE POSITION
- 016 GPS CODE (PSEUDO RANGE) STANDARD POSITION (SA OFF)
- 017 GPS CODE (PSEUDO RANGE) STANDARD POSITION (SA ON)
- 018 INTERPOLATION-MAP
- 019 INTERPOLATION-PHOTO
- 020 INTERPOLATION-SATELLITE
- 021 INTERPOLATION-OTHER
- 022 LORAN C
- 023 PUBLIC-LAND-SURVEY-QUARTER SECTION
- 024 PUBLIC-LAND-SURVEY-FOOTING
- 025 CLASSICAL SURVEYING TECHNIQUES
- 026 ZIP CODE-CENTROID
- 027 UNKNOWN
- 028 GPS UNSPECIFIED
- 029 GPS WITH CANADIAN ACTINVE CONTROL SYSTEM
- 030 INTERPOLATION DIGITAL MAP SRCE (TIGER)
- 031 INTERPOLATION SPOT
- 032 INTERPOLATION-MSS
- 033 INTERPOLATION-TM
- 034 PUBLIC LAND SURVEY EIGHTH SECTION
- 035 PUBLIC LAND SURVEY SIXTEENTH SECTION
- 036 PUBLIC LAND SURVEY FOOTING
- 037 ZIP+4 CENTROID
- 038 ZIP+2 CENTROID

4.1.12 LDP Horizontal Datum

Description: The edition of North American Datum used as the basis for determining the

site coordinates. (The editions of North American Datum establish a network of monuments and reference points defining a mathematical surface from which geographic computations can be made.) The World Geodetic Survey 1984 (WGS84) is one horizontal datum used by many Global Positioning System (GPS) instruments. United States Geological Survey (USGS) maps

often use the North Atlantic Datum 1927 (NAD27).

This data element is required by EPA Locational Data Policy. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website

(http://www.epa.gov/edr/).

Attributes: Alphanumeric

Up to 120 characters

Mandatory

Coding Instructions: Place a valid LDP horizontal datum value in the twelfth delimited field. A

value is valid if it is in the LDP Horizontal Data Table. Examples of LDP Horizontal Datum values as of September 11, 2003 are given below:

Horiz Datum	Status	Inc
NAD27		P
NAD83		P
NAD84		I
UNKNOWN		I
WGS84		P

Note: A status indicator of I means that old data could have these values, but new data cannot use these values. (I = inactive, P = production)

4.1.13 LDP Source Scale

Description: Identifies the ratio of the map or cartographic product to the true location.

The data element for scale should be the X value of the 1:X ratio (e.g., if the scale is 1:24,000, the value of the scale data element should be 24,000). The United States Geological Survey 1:24,000 is usually the smallest reasonable scale for locating sub-facility points, such as stacks or pipes. The relative accuracies of maps as a locational tool decreases as the X value increases. This field is required when the Horizontal Collection Method is based upon using a map. This data element is required by EPA Locational Data Policy. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website

(http://www.epa.gov/edr/).

Attributes: Numeric

12 digits (nnnnnnnnnn)

Mandatory

Coding Instructions: Place a valid LDP source scale value in the thirteenth delimited field.

4.1.14 LDP Measurement Accuracy Value

Description: Description of the accuracy of the site coordinates, as a range reported in

meters. Only the least accurate measurement needs to be recorded, whether

it is latitude or longitude (or UTM easting or northing).

For example, here are accuracy standards for various scale maps, assuming that the maps conform to the national mapping accuracy standards:

 $1:1,200 \pm 3.33$ feet $1:2,400 \pm 6.67$ feet $1:4.800 \pm 13.33$ feet $1:10,000 \pm 27.78$ feet $1:12,000 \pm 33.33$ feet $1:24,000 \pm 40.00$ feet $1:63,360 \pm 105.60$ feet $1:100,000 \pm 166.67$ feet

Map interpolation would also introduce error.

For GPS, the accuracy values vary. The type of GPS used along with operating conditions affect accuracy. The GPS receiver may provide accuracy values associated with specific coordinate readings.

This data element is required by EPA Locational Data Policy (LDP). More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (http://www.epa.gov/edr/).

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Mandatory

Coding Instructions: Place the LDP measurement accuracy value in the fourteenth delimited field.

4.1.15 LDP Vertical Measure

Description: The elevation, in meters, above or below mean sea level (MSL) of the site.

Required by EPA Locational Data Policy (LDP). More information regarding EPA's data standards and policies may be found on EPA's Environmental

Data Registry (EDR) Website (http://www.epa.gov/edr/).

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Mandatory

Coding Instructions: Place a numeric value in the fifteenth delimited field.

4.1.16 Time Zone

Description: A standard time zone, as established by section 1 of the Standard Time Act,

as amended by section 4 of the Uniform Time Act of 1966 (15 U.S.C. 261).

Attributes: Alphanumeric

Up to 30 characters

Optional

Coding Instructions: To insert or update a time zone, place a valid value in the sixteenth delimited

field. A time zone value is valid if it exists in combination with state code

in the State Time Zones Table.

4.1.17 Support Agency

Description: Identifies the agency responsible for the operation of the monitoring site.

Attributes: Alphanumeric

4-digit code

Optional (Mandatory for insert)

Coding Instructions: To insert or update, place a valid agency code in the seventeenth delimited

field. A support agency value is valid if it exists in combination with the

state code value in the State Agencies Table.

4.1.18 Street Address

Description: Specifies the building/street location of the monitoring site.

Attributes: Alphanumeric

Up to 2000 characters

Mandatory

Coding Instructions: Place street address text in the eighteenth delimited field. Any non-blank

value is valid.

4.1.19 City Code

Description: The city within whose legal boundaries the monitoring site is located.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid FIPS city code value in the nineteenth delimited field. A city

code value is valid if it exists in combination with state code and county code in the County Cities Table. If the site is not within a city, use code 00000.

4.1.20 Urban Area Code

Description: The urbanized area within which the monitoring site is located. An urbanized

area is a U.S. Census Bureau demographic entity that comprises a place and the adjacent densely-settled surrounding territory that together have a minimum population of 50,000 people.

Attributes: Alphanumeric

4-digit code Mandatory

Coding Instructions: Place a valid urban area code value in the twentieth delimited field. An

urban area code value is valid if it exists in combination with state code in the State Urbanized Areas Table. If the monitoring site is not within an

urbanized area, use code 0000.

4.1.21 AQCR

Description: Specifies in which of the 247 Air Quality Control Regions (AQCRs) the

monitoring site is located.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: To insert or update AQCR, place a valid AQCR code in the twenty-first

delimited field. A valid AQCR code is one that, in combination with state

code and county code, exists in the AQCR Counties Table.

4.1.22 Land Use

Description: Categorization of the prevalent land use within 1/4 mile of the monitoring

site.

Attributes: Alphanumeric

Up to 20 characters

Mandatory

Coding Instructions: Place a valid land use type term in the twenty-second delimited field. A land

use term is valid if it exists in the Land Use Types Table.

4.1.23 Location Setting

Description: A description of the environmental setting within which the site is located.

Attributes: Alphanumeric

Up to 50 characters

Mandatory

Coding Instructions: Place a valid location setting term in the twenty-third delimited field. A

location setting term is valid if it exists in the Location Settings Table.

4.1.24 Date Site Established

Description: The date on which an air monitoring site began collecting air quality data.

Attributes: Date

8-digit date Optional

Coding Instructions: Place a date, using the format YYYYMMDD, in the twenty-fourth delimited

field. The date must be between January 1, 1957 and a year after the current

date.

4.1.25 Date Site Terminated

Description: The date on which a monitoring site ceased to operate.

Attributes: Date

8-digit date Optional

Coding Instructions: Place a date, using the format YYYYMMDD, in the twenty-fifth delimited

field. The date must be between January 1, 1957 and the current date, and must be greater than date site established. All monitors at a site must have

a date sampling ended before a site can be terminated.

4.1.26 ZIP Code

Description: The U.S. Postal Service Zone Improvement Plan (ZIP) Code used to address

the monitoring site.

Attributes: Alphanumeric

5- or 9-digit code

Optional

Coding Instructions: Place a valid 5-digit or 9-digit ZIP Code in the twenty-sixth delimited field.

A ZIP Code value is valid if it exists in combination with state code and

county code in the County ZIP Codes Table.

4.1.27 Congressional District

Description: The Congressional district within which the site is located.

Attributes: Alphanumeric

2-digit code Optional

Coding Instructions: Place a valid Congressional district number in the twenty-seventh delimited

field. A Congressional district value is valid if it exists in combination with state code in the Congressional Districts Table. If there is only one Congressional district in a state (in which case the district is not numbered),

enter the value of 1.

4.1.28 Block

Description: The U.S. Census Bureau block within which the site is located.

Attributes: Alphanumeric

4-digit code Optional

Coding Instructions: Block information must be submitted in conjunction with block group and

census tract. Place a valid block number in the twenty-eighth delimited field. A block value is valid if it exists in combination with state code, county code,

block group, and census tract in the Blocks Table.

4.1.29 Block Group

Description: The U.S. Census Bureau block group within which the site is located.

Attributes: Alphanumeric

1-digit code Optional

Coding Instructions: Block group information must be submitted in conjunction with block and

census tract. Place a valid block group number in the twenty-ninth delimited field. A block group value is valid if it exists in combination with state code,

county code, block, and census tract in the Blocks Table.

4.1.30 Census Tract

Description: The U.S. Census Bureau census tract/block numbering area within which the

site is located.

Attributes: Alphanumeric

3- to 6-digit code

Optional

Coding Instructions: Census tract information must be submitted in conjunction with block and

block group. Place a valid census tract code in the thirtieth delimited field. A census tract value is valid if it exists in combination with state code, county

code, block, and block group in the Blocks Table.

4.1.31 Class I Area

Description: The Class One Area within which the site is located. A Class One Area is a

geographic area recognized by EPA as being of the highest environmental

quality and requiring maximum protection.

Attributes: Alphanumeric

6-character code

Optional

Coding Instructions: Place a valid Class One Area code in the thirty-first delimited field. A Class

One Area code is valid if it exists in the Class One Areas Table.

4.1.32 Local Region

Description: The state-specific geographic/administrative area within which the site is

located.

Attributes: Alphanumeric

1- to 2-digit code

Optional

Coding Instructions: Place a valid local region code in the thirty-second delimited field. A local

region code is valid if it exists in combination with state code in the Local

Regions Table.

4.1.33 Local Site Name

Description: The locally defined name of the site.

Attributes: Alphanumeric

Up to 70 characters

Optional

Coding Instructions: Place a text description of the locally-defined site name in the thirty-third

delimited field. Any non-blank value is valid.

4.1.34 HQ Evaluation Date

Description: The date on which the most recent headquarters (HQ) evaluation of the site

occurred.

Attributes: Date

8-digit date Optional

Coding Instructions: Place a date, in the format YYYYMMDD, in the thirty-fourth delimited field.

To be valid, HQ evaluation date must be between January 1, 1980 (when the National Air Monitoring Sites Regulations were published) and the current

date.

4.1.35 Regional Evaluation Date

Description: The date on which the most recent regional evaluation of the site for siting

criteria occurred.

Attributes: Date

8-digit date Optional

Coding Instructions: Place a date, in the format YYYYMMDD, in the thirty-fifth delimited field.

To be valid, regional evaluation date must be between January 1, 1980 (when the National Air Monitoring Sites Regulations were published) and the

current date.

4.1.36 Compass Sector

Description: A representation of the true, as opposed to magnetic, direction of the site

from the central business district. If the site is within the central business

district, it is a representation of the direction the probe faces.

Attributes: Alphanumeric

Up to 3-character code

Optional

Coding Instructions: Place a valid compass sector value in the thirty-sixth delimited field. A

compass sector value is valid if it exists in the Compass Sectors Table.

4.1.37 Distance to City

Description: The distance, in kilometers, to the site from the center of the downtown

central business district of the city in which the site is located.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Optional

Coding Instructions: Place a numeric value greater than 0 and less than 1000 in the thirty-seventh

delimited field.

4.1.38 Type Meteorological Site

Description: The type of meteorological station identified for the monitoring site.

Required for sites with monitors in a Photochemical Assessment Monitoring

System (PAMS) network.

Attributes: Alphanumeric

Up to 20 characters

Optional

Coding Instructions: Place a valid type meteorological site in the thirty-eighth delimited field. A

type meteorological site value is valid if it exists in the Met Site Types Table.

4.1.39 Meteorological Site ID

Description: The AQS site ID where meteorological data is collected, if not collected at

this site.

Attributes: Alphanumeric

9-digit ID Optional

Coding Instructions: Place a valid AQS site ID in the thirty-ninth delimited field. The format for

AQS site ID is a joining of a FIPS state code (2 numeric characters), a FIPS county code (3 numeric characters), and 4-digit site ID. A meteorological site ID value is valid if it represents an existing site (a row on the Sites Table),

and type meteorological site is other AQS site.

4.1.40 Distance to Meteorological Site

Description: The distance of the associated meteorological site from the air quality

monitoring site, in meters. This information is required if the site has monitors that are part of a Photochemical Assessment Monitoring System

(PAMS) network. The associated site need not be a AQS site.

Attributes: Numeric

8 digits, including 2 decimal places (nnnnn.nn)

Optional

Coding Instructions: Place a valid numeric distance to meteorological site value in the fortieth

delimited field. The distance to meteorological site is valid if it is greater than 0 and type meteorological site is not on-site met equip and not on-site Upper Air meteorological site (UA met). A distance to meteorological site value may be nullified, if type meteorological site is nullified, on-site met

equip, or on-site UA met.

4.1.41 Direction to Meteorological Site

Description: A representation of the true, as opposed to magnetic, direction of the

meteorological site from this site.

Attributes: Alphanumeric

Up to 3-character code

Optional

Coding Instructions: Place a valid direction to met site value in the forty-first delimited field. A

direction to met site value is valid if it exists in the Compass Sectors Table and type meteorological site is not on-site met equip and not on-site Upper Air meteorological site (UA met). A direction to met site value may be nullified, if type meteorological site is nullified, on-site met equip or on-site

UA met.

4.1.42 State or Local ID

Description: Identification code used by a state or local agency, if different from the AQS

site ID.

Attributes: Alphanumeric

Up to 40 characters

Optional

Coding Instructions: Place an alphanumeric value in the forty-second delimited field. No edit

checks are performed.

4.1.43 LDP Vertical Method

Description: The method used to determine the Locational Data Policy (LDP) vertical

measure. This data element is required by EPA LDP. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (http://www.epa.gov/edr/).

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid LDP vertical method code in the forty-third delimited field.

View vertical method code descriptions in the Appendices, or via Discoverer, and choose the appropriate code. Examples of the LDP Vertical Method

Codes as of September 11, 2003 are given below:

Code Description

001 GPS CARRIER PHASE STATIC RELATIVE POSITION

002 GPS CARRIER PHASE KINEMATIC RELATIVE POSITION

003 GPS CODE (PSEUDO RANGE) DIFFERENTIAL

004 GPS CODE (PSEUDO RANGE)PRECISE POSITION

005 GPS CODE (PSEUDO RANGE)STANDARD POSITION (SA OFF)

006 GPS CODE (PSEUDO RANGE)STANDARD POSITION (SA ON)

007 CLASSICAL SURVEYING TECHNIQUES

008 OTHER

009 ALTIMERY

010 PRECISE LEVELING-BENCH MARK

011 LEVELING-NON BENCH MARK CONTROL POINTS

012 TRIGONOMETRIC LEVELING

013 PHOTOGRAMMETRIC

014 TOPOGRAPHIC MAP INTERPOLATION

000 UNKNOWN

4.1.44 LDP Vertical Datum

Description: The edition of North American Datum used as the basis for determining the

site coordinates. (The editions of North American Datum establish a network of monuments and reference points defining a mathematical surface from which geographic computations can be made.) This data element is required by EPA Locational Data Policy (LDP). More information regarding EPA's data standards and policies may be found on EPA's Environmental Data

Registry (EDR) Website (http://www.epa.gov/edr/).

Attributes: Alphanumeric

Up to 120 characters

Mandatory

Coding Instructions: Place a valid LDP vertical datum value in the forty-fourth delimited field. A

value is valid if it is in the LDP Vertical Data Table. Examples of the LDP

Vertical Datum Values as of September 11, 2003 are given below:

LDP Vertical Datum

NAVD88 NGVD29

MEAN SEA-LEVEL LOCAL TIDAL DATUM

UNKNOWN

4.1.45 LDP Vertical Accuracy Value

Description: Description of the accuracy of the LDP vertical measure, reported in meters.

This data element is required by EPA Locational Data Policy (LDP). More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website

(http://www.epa.gov/edr/).

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Mandatory

Coding Instructions: Place the LDP vertical accuracy value in the forty-fifth delimited field.

4.2 SITE STREET INFORMATION - TRANSACTION TYPE AB

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors.

See the data input transaction formats in the Appendices for a list of required fields for each transaction format.

4.2.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

4.2.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

4.2.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

4.2.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

> as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

> 3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

4.2.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether

a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing

for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID

Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

4.2.6 Tangent Street Number

Description: Identifies the number of the street around the site for which the data are being

submitted. If street name, type road, traffic flow, year of traffic flow, or direction to street is valued, street number must be valued. Street number is used to associate detailed street information for the site to streets closest to

the monitors at this site.

Attributes: Numeric

2 digits (nn) Mandatory

Coding Instructions: Place a valid number in the sixth delimited field.

4.2.7 Street Name

Description: The name of the street closest to the monitoring site.

Attributes: Alphanumeric

Up to 50 characters

Mandatory

Coding Instructions: Place the street name in the seventh delimited field.

4.2.8 Type Road

Description: The type of road or street being described.

Attributes: Alphanumeric

Up to 20 characters

Mandatory

Coding Instructions: Place a valid type road term in the eighth delimited field. A type road value

is valid if it exists on the Road Types Table.

4.2.9 Traffic Count

Description: An estimate of the daily traffic volume on the roadway.

Attributes: Numeric

12 digits (nnnnnnnnnn)

Mandatory

Coding Instructions: Place a valid traffic count in the ninth delimited field. A traffic count value

is valid if it is greater than 0.

4.2.10 Year of Traffic Count

Description: The year when the traffic count value was estimated.

Attributes: Date

4-digit year (yyyy)

Mandatory

Coding Instructions: Place a valid year of traffic count in the tenth delimited field. A year of

traffic count value is valid if it is greater than 1957 and less than or equal to

the current year.

4.2.11 Direction to Street

Description: The direction from the site to the street at its nearest point.

Attributes: Alphanumeric

3-character code Mandatory

Coding Instructions: Place a valid direction to street in the eleventh delimited field. A direction

to street value is valid if exists on the Compass Sectors Table.

4.2.12 Source of Traffic Count

Description: The method by which the traffic volume/flow count was obtained.

Attributes: Numeric

10 digits (nnnnnnnnn)

Optional

Coding Instructions: Enter a valid source of traffic count code in the twelfth delimited field. A

source of traffic count value is valid if it exists on the Traffic Volume Sources Table.

4.3 SITE OPEN PATH INFORMATION - TRANSACTION TYPE AC

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors. See the data input transaction formats in the Appendices for a list of required fields for each transaction format.

4.3.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

4.3.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

4.3.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

4.3.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

4.3.5 Site ID

Attributes:

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether

a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing for that combination of state ID and county code.

Alphanumeric

4-digit ID Mandatory Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

4.3.6 Open Path Number

Description: A unique numeric identifier for the individual open path at a site. Each open

path represents a different monitor.

Attributes: Numeric

2 digits (nn) Mandatory

Coding Instructions: Place a valid open path number in the sixth delimited field. An open path

number value is valid if it is between 1 and 99.

4.3.7 Direction to Transmitter

Description: The direction from the receiver to the transmitter at the site.

Attributes: Alphanumeric

Up to 3-character code

Mandatory

Coding Instructions: Place a valid direction to transmitter in the seventh delimited field. A

direction to transmitter value is valid if it exists on the Compass Sectors

Table.

4.3.8 Beam Length

Description: The length of the beam projected between the transmitter and the receiver at

the site, in meters.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Mandatory

Coding Instructions: Place a valid beam length in the eighth delimited field. A beam length value

is valid if it is greater than 0.

4.3.9 Height of Transmitter

Description: The height of the transmitter above the ground, in meters.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Mandatory

Coding Instructions: Place a valid height of transmitter in the ninth delimited field. A height of

transmitter value is valid if it is greater than 0.

4.3.10 Height of Receiver

Description: The height of the receiver above the ground, in meters.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Mandatory

Coding Instructions: Place a valid height of receiver in the tenth delimited field. A height of

receiver value is valid if it is greater than 0.

4.3.11 Minimum Height

Description: The height of the beam (at the lowest point from the ground) being projected

between the receiver and transmitter at the site, in meters.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Mandatory

Coding Instructions: Place a valid minimum height value in the eleventh delimited field. A

minimum height value is valid if it is greater than 0 and less than maximum

height.

4.3.12 Maximum Height

Description: The height of the beam (at the highest point from the ground) being projected

between the receiver and transmitter at the site, in meters.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Mandatory

Coding Instructions: Place a valid Maximum height value in the twelfth delimited field. A

maximum height value is valid if it is greater than 0 and greater than

minimum height.

4.3.13 Land Use under Path

Description: The prevalent land use under the path of the beam being projected between

the receiver and transmitter at the site.

Attributes: Alphanumeric

Up to 20 characters

Mandatory

Coding Instructions: Place a valid land use under path description in the thirteenth delimited field.

A land use under path value is valid if it exists on the Land Use Types Table.

4.4 SITE COMMENTS (Online Update Only)

Description: Site comments is a free-format field that may be used in any way desired. It

is commonly used to describe special features of a site. Multiple lines can be

created by incrementing the sequence number. Online update only.

Attributes: 68 characters

Optional

Coding Instructions: To insert or update, place the appropriate text in the comment fields using the

maintain screen.

5.0 MONITOR TRANSACTIONS (MA - MK)

This set of eleven transactions is used to update monitor information in the site file.

Type MA, Basic Monitor Information, performs data manipulation on the Monitors and Pollutant Area Monitors Tables, and contains the following fields:

Transaction Type Vertical Distance

Action Code Surrogate Flag Indicator

State Code Unrestricted Air Flow Indicator

County Code Sample Residence Time

Site ID Worst Site Type

Parameter Applicable NAAQS Indicator
POC Spatial Average Indicator
Project Class Schedule Exemption Indicator
Dominant Source Community Monitoring Zone

Measurement Scale

Open Path Number

Pollutant Area Code – 1

Probe Location Code

Probe Height

Pollutant Area Code – 3

Probe Height

Pollutant Area Code – 4

Horizontal Distance

Pollutant Area Code – 5

Type MB, Monitor Sampling Periods, performs data manipulation on the Sample Periods Table, and contains the following fields:

Transaction Type Parameter Action Code POC

State Code Date Sampling Began
County Code Date Sampling Ended

Site ID

Type MC, Monitor Type Information, performs data manipulation on the Monitor Type Assignments Table, and contains the following fields:

Transaction Type Parameter Action Code POC

State Code Monitor Type

County Code Monitor Type Begin Date
Site ID Monitor Type End Date

Type MD, Monitor Agency Role, performs data manipulation on the Agency Roles Table, and contains the following fields:

Transaction Type POC

Action Code Agency Role Name
State Code Agency Code
County Code Begin Date
Site ID End Date

Parameter

Type ME, Monitoring Objective Information, performs data manipulation on the Monitor Objectives Table, and contains the following fields:

Transaction Type POC

Action Code Monitor Objective
State Code Urban Area Represented
County Code MSA Represented
Site ID CMSA Represented

Parameter

Type MF, Monitor Sampling Schedule, performs data manipulation on the Req Coll Frequencies and Sample Schedules Tables, and contains the following fields:

Transaction Type RCF Code
Action Code RCF Begin Date
State Code RCF End Date

County Code Collection Frequency January - December (12

Site ID instances)

Parameter POC

Type MG, Monitor Street Description, performs data manipulation on the Monitor Tangent Roads Table, and contains the following fields:

Transaction Type Parameter Action Code POC

State Code Tangent Street Number County Code Distance from Monitor

Site ID

Type MH, Monitor Obstruction Information, performs data manipulation on the Probe Obstructions Table, and contains the following fields:

Transaction Type State Code
Action Code County Code

Site ID Parameter POC Direction from Monitor Distance to Monitor Height of Obstruction

Type Obstruction

Type MI, Monitor Regulatory Compliance, performs data manipulation on the Regulation Compliances Table, and contains the following fields:

Transaction Type Parameter Action Code POC

State Code Monitor Regulation Code
County Code Compliance Indicator
Site ID Compliance Date

Type MJ, Monitor Collocation Period, performs data manipulation on the Monitor Collocations Table, and contains the following fields:

Transaction Type POC

Action Code Collocation Begin Date
State Code Collocation End Date

County Code Distance from Primary Monitor
Site ID Primary Monitor Indicator

Parameter

Type MK, Monitor Protocol performs data manipulation on the Monitor Protocols Table, and contains the following fields:

Transaction Type Alternate MDL ID
Action Code Sample Duration

State Code Unit
County Code Method

Site ID Collection Frequency
Parameter Composite Type

POC Minimum Detect Value

Transactions are used to create a monitor that does not already exist on the Site Table. Transaction Types MA, MB, MC, MD, and ME are required to create a new monitor for criteria pollutants. To insert a new monitor, either its parent site must already exist in the database, or the parent site must be created at the same time as the site transactions in the batch file. See the transaction requirements and data input formats in the Appendices for specific requirements.

Transactions are used to remove a monitor from the site file. The delete action code is allowed only

for type AA transactions.

Transactions are used to change information in the site file for existing monitors. The values coded on an update transaction replace the values of the corresponding fields in the monitor record of the site file. If no value existed previously, the value from the transaction is inserted into the monitor record. Some fields are required, and cannot be deleted. They are identified in the coding instructions that follow, and in transaction formats.

5.1 BASIC MONITOR INFORMATION - TRANSACTION TYPE MA

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors.

See the data input transaction formats in the Appendices for a list of required fields on each transaction format. For criteria pollutant monitors, transaction types MA through ME are required.

5.1.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

5.1.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

5.1.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

5.1.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

5.1.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether

a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing

for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

5.1.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter code

is valid if the code exists in the Parameters Table.

5.1.7 POC (Parameter Occurrence Code)

Description: An identifier used to distinguish between multiple monitors at the same site

that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple

samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit ID Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

5.1.8 Project Class

Description: The type of sampling performed by the monitor.

Attributes: Alphanumeric

2-digit code Optional

Coding Instructions: Place a valid project class code in the eighth delimited field. A project class

value is valid if it exists in the Project Types Table.

5.1.9 Dominant Source

Description: The primary source of the pollutant being measured.

Attributes: Alphanumeric

Up to 20 characters

Optional

Coding Instructions: Place a valid dominant source term in the ninth delimited field. A dominant

source value is valid if it exists in the Dominant Sources Table.

5.1.10 Measurement Scale

Description: A denotation of the geographic scope of the air quality measurements made

by the monitor. The implication is that the same measurement made elsewhere within the measurement scale would produce an equivalent result

to that produced at the monitoring site.

Attributes: Alphanumeric

Up to 20 characters

Optional

Coding Instruction: Place a valid measurement scale term in the tenth delimited field. A

measurement scale term is valid if it exists in the Measurement Scales Table.

5.1.11 Open Path Number

Description: The specific open path number registered at the site that the monitoring data

and monitor represent. The number must be registered at the site before it

can be identified by the monitor.

Attributes: Numeric

2 digits (nn) Optional

Coding Instructions: Place a valid open path number in the eleventh delimited field. An open path

number value is valid if it exists in combination with state code, county code,

and site ID on the Open Paths Table.

5.1.12 Probe Location Code

Description: The location of the sampling probe.

Attributes: Alphanumeric

Up to 20 characters

Optional

Coding Instructions: Place a valid probe location term in the twelfth delimited field. A probe

location term is valid if it exists in the Probe Locations Table.

5.1.13 Probe Height

Description: The height of the sampling probe from the ground in meters.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Optional:

Required on insert Optional on update May not be deleted

Coding Instructions: Place a valid probe height value in the thirteenth delimited field. A probe

height value is valid if it is greater than 0.

5.1.14 Horizontal Distance

Description: The horizontal distance, in meters, of the probe from its supports.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Optional:

Required on insert Optional on update May not be deleted

Coding Instructions: Place a valid probe horizontal distance value in the fourteenth delimited field.

A horizontal distance value is valid if it is greater than 0.

5.1.15 Vertical Distance

Description: The vertical distance, in meters, of the probe from its supports.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Optional:

Required on insert Optional on update May not be deleted

Coding Instructions: Place a valid probe vertical distance value in the fifteenth delimited field. A

vertical distance value is valid if it is greater than 0.

5.1.16 Surrogate Flag Indicator

Description: Indicates whether a Total Suspended Particulate (TSP) monitor serves as a

surrogate monitor for PM-10.

Attributes: 1-character code: Y or N

Optional:

Required for TSP insert Optional for TSP update Prohibited if not TSP May not be deleted

Coding Instructions: If parameter is 11101 and the monitor is a surrogate for PM-10, then place the

value Y in the sixteenth delimited field.

If parameter is not 11101, or parameter is 11101, but the monitor is not a surrogate for PM-10, place nothing or N in the sixteenth delimited field.

5.1.17 Unrestricted Air Flow Indicator

Description: Indication of whether the flow of air to the monitor is restricted.

Attributes: Alphanumeric

1-character code: Y, N, or W

Optional

Coding Instructions: Place a valid unrestricted air flow indicator in the seventeenth delimited field.

An unrestricted air flow indicator value is valid if it is Y (for yes), N (for no),

or W (for waiver).

5.1.18 Sample Residence Time

Description: The time in seconds for the sample to move from the probe inlet to the

monitor.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Optional

Coding Instructions: Place a valid sample residence time in the eighteenth delimited field. A

sample residence time value is valid if it is greater than 0.

5.1.19 Worst Site Type

Description: Within a particular monitoring area, those monitors with the highest PM-10

concentrations must have their worst site type set to 1, and are expected to monitor at the recommended collection frequency. Other monitors must be classified as either not worst site monitors, or monitoring on an accelerated

schedule, but not at the recommended collection frequency.

Attributes: Alphanumeric

1-digit code Optional:

> Required for PM-10 insert Optional for PM-10 update Prohibited if not PM-10 May not be deleted

Coding Instructions: Place a valid worst site type code in the nineteenth delimited field.

For an insert, a worst site type value is valid if it exists in the Worst Site Types Table and one of the following is populated with a monitoring area code: pollutant area code 1, pollutant area code 2, pollutant area code 3,

pollutant area code 4, or pollutant area code 5.

For an update, a worst site type value is valid if it exists in the Worst Site Types Table and one of the following is populated with a monitoring area code: pollutant area code 1, pollutant area code 2, pollutant area code 3, pollutant area code 4, or pollutant area code 5, or there is an existing monitoring area code for the monitor on the Pollutant Area Monitors Table. If either pollutant area code 1, pollutant area code 2, pollutant area code 3, pollutant area code 4, or pollutant area code 5 are populated with a monitoring area code, then worst site type is required.

5.1.20 Applicable NAAQS Indicator

Description: The applicable NAAQS (National Ambient Air Quality Standards) indicator

> determines whether the data from a monitor in a monitor planning area should be compared to either the short-term or annual NAAQS, or both.

Attributes: Alphanumeric

1-character code

Optional

Coding Instructions: Place a valid applicable NAAQS indicator in the twentieth delimited field.

> An applicable NAAQS indicator value is valid if it is S (for short-term), A (for annual), or B (for both), and one of the following is populated with a monitor planning area code: pollutant area code 1, pollutant area code 2,

pollutant area code 3, pollutant area code 4, or pollutant area code 5.

5.1.21 Spatial Average Indicator

Description: Indicates whether spatial averaging is to be performed for the all individual

annual weighted means for sites that are flagged and in the same community

monitoring zone.

Attributes: Alphanumeric

1-character code

Optional

Coding Instructions: Place a valid spatial average indicator in the twenty-first delimited field. A

spatial average indicator value is valid if:

1) it is Y (for yes), or N (for no),

2) one of the following is populated with a monitor planning area code:

pollutant area code 1, pollutant area code 2, pollutant area code 3, pollutant

area code 4, or pollutant area code 5, and

3) community monitoring zone is assigned a value.

5.1.22 Schedule Exemption Indicator

Description: Indicates whether the sampling schedule differs from that required by the

standard by approval of the Regional Administrator.

Attributes: 1-character code: Y or N

Optional

Coding Instructions: Place a valid schedule exemption indicator in the twenty-second delimited

field. A schedule exemption indicator value is valid if it is Y (for yes) or N (for no), and one of the following is populated with a monitor planning area code: pollutant area code 1, pollutant area code 2, pollutant area code 3,

pollutant area code 4, or pollutant area code 5.

5.1.23 Community Monitoring Zone

Description: A sequential number assigned to an optional averaging area with an

established, defined boundary within a monitor planning area that has a relatively uniform concentration of annual PM-2.5. Community monitoring

zones do not cross geographical lines.

Attributes: Numeric

4 digits (nnnn)
Optional

Coding Instructions: Place a valid community monitoring zone number in the twenty-third

delimited field. A community monitoring zone value is valid if one of the following is populated with a monitor planning area code: pollutant area code 1, pollutant area code 2, pollutant area code 3, pollutant area code 4, or

pollutant area code 5.

5.1.24 Pollutant Area Code 1, 2, 3, 4, or 5

Description: Designation of pollutant areas to which the monitor is assigned. Using these

fields, up to five pollutant areas can be designated for an individual monitor. Pollutant areas are geographic areas defined by a program office in which a certain pollutant should be closely watched. Most are problem or non-attainment areas, but attainment areas requiring special attention may also be defined. Types of pollutant areas are status areas, monitoring areas,

and monitor planning areas.

Attributes: Alphanumeric

5-character code

Optional

Coding Instructions:

The transaction format allows the designation of up to five pollutant areas. The delimited fields allocated for these designations are positions 24-28. Assignments should be made in sequence, i.e., do not use position 25, if you have not yet used position 24. Only one pollutant area code for each pollutant area type may be assigned to a single monitor. (It is valid to assign one monitoring area and one status area; it is not valid to assign two monitoring areas.)

To insert, place a valid pollutant area code in the next available field (24-28). A pollutant area code value is valid if it exists on the Pollutant Areas Table, and its pollutant area type is valid for the assigned value of parameter.

5.2 MONITOR SAMPLING PERIODS - TRANSACTION TYPE MB

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors. See the data input transaction formats in the Appendices for a list of required fields on each transaction format. For criteria pollutant monitors, transaction types MA through ME are required.

Multiple sampling periods may be registered in the database to allow for definition of periodic monitoring. The edit restrictions prevent more than one sampling period from having a blank date sampling ended.

The fields described below are validated for insert (I) and update (U) transactions.

5.2.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

5.2.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

5.2.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

5.2.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

5.2.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether

a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to

ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with State code and

county code in the Sites Table.

5.2.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

5.2.7 POC (Parameter Occurrence Code)

Description: An identifier used to distinguish between multiple monitors at the same site

that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are

reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit ID Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

5.2.8 Date Sampling Began

Description: The date on which a distinct period of operations, i.e., collection of air quality

samples, began for the monitor.

Attributes: Date

8-digit date Mandatory

Coding Instructions: Place a valid date string in the eighth delimited field. A date sampling began

value is valid if it: is in the format of YYYYMMDD, is between January 1, 1957 and one year from the current date, does not fall within any other sample periods defined for the monitor, is greater than or equal to the date site established for the corresponding site, and is less than or equal to the date

site terminated for the corresponding site, if populated.

5.2.9 Date Sampling Ended

Description: The date on which a distinct period of operations, i.e., collection of air quality

samples, stopped for the monitor.

Attributes: Date

8-digit date Optional

Coding Instructions: Place a valid date string in the ninth delimited field. A date sampling ended

value is valid if it: is in the format of YYYYMMDD, is between January 1, 1957 and one year from the current date, is greater than or equal to the specified date sampling began, does not fall within any other sample periods defined for the monitor, is greater than or equal to the date site established for the corresponding site, and is less than or equal to the date site terminated for

the corresponding site, if populated..

5.3 MONITOR TYPE INFORMATION - TRANSACTION TYPE MC

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors. See the data input transaction formats in the Appendices for a list of required fields on each transaction format. For criteria pollutant monitors, transaction types MA through ME are required.

The fields described below are validated for insert (I) and update (U) transactions.

5.3.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

5.3.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

5.3.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

5.3.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

5.3.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing

for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

5.3.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

5.3.7 POC (Parameter Occurrence Code)

Description: An identifier used to distinguish between multiple monitors at the same site

that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple

samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit ID Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

5.3.8 Monitor Type

Description: The monitor's administrative classification.

Attributes: Alphanumeric

20-character code

Mandatory

Coding Instructions: Place a valid monitor type term in the eighth delimited field. A monitor type

value is valid if it exists in the Monitor Types Table.

5.3.9 Monitor Type Begin Date

Description: The date on which the monitor type assignment went into effect.

Attributes: Date

8-digit date Mandatory

Coding Instructions: Place a valid date string in the ninth delimited field. A monitor type begin

date value is valid if it: is in the format of YYYYMMDD, the monitor type is National Air Monitoring System (NAMS) or State and Local Air Monitoring System (SLAMS) and is between January 1, 1980 and one year from the current date, the monitor type is not NAMS or SLAMS and is between January 1, 1957 and one year from the current date, does not fall within any other monitor type assignment periods defined for the monitor for the same monitor type, and falls within a sample period for the monitor.

5.3.10 Monitor Type End Date

Description: The date on which a monitor type assignment ends.

Attributes: Date

8-digit date Optional

Coding Instructions:

Place a valid date string in the tenth delimited field. A monitor type end date value is valid if it: is in the format of YYYYMMDD, is greater than the monitor type begin date, the monitor type is National Air Monitoring System (NAMS) or State and Local Air Monitoring System (SLAMS) and is between January 1, 1980 and one year from the current date, the monitor type is not NAMS or SLAMS and is between January 1, 1957 and one year from the current date, does not fall within any other monitor type assignment periods defined for the monitor for the same monitor type, and falls within a sample period for the monitor. Multiple monitor type designations with a blank monitor type end date are valid. By definition, a NAMS is also a SLAMS, and a Photochemical Assessment Monitoring System (PAMS) can also be a NAMS or SLAMS.

5.4 MONITOR AGENCY ROLE - TRANSACTION TYPE MD

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors. See the data input transaction formats in the Appendices for a list of required fields on each transaction format. For criteria pollutant monitors, transaction types MA through ME are required.

The fields described below are validated for insert (I) and update (U) transactions.

5.4.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

5.4.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

5.4.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

5.4.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

5.4.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing

for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with State code and

county code in the Sites Table.

5.4.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

5.4.7 POC (Parameter Occurrence Code)

Description: An identifier used to distinguish between multiple monitors at the same site

that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple

samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit ID Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

5.4.8 Agency Role Name

Description: Classification of an agency's role in regard to the monitor.

Attributes: Alphanumeric

20 characters Mandatory

Coding Instructions: Place a valid agency role term in the eighth delimited field. A role name

value is valid if it exists in the Agency Roles Table with the role type of monitor. Multiple agency role names with the same value cannot be entered for the same period. If the agency changes for any role, the begin and end

dates are used to define the applicable time period.

5.4.9 Agency Code

Description: Identification of an agency responsible for performing a role for the monitor.

Attributes: Alphanumeric

4-digit code Mandatory

Coding Instructions: To insert or update, place a valid agency code in the ninth delimited field. An

agency code value is valid if it exists in combination with the state code value

in the State Agencies Table.

5.4.10 Begin Date

Description: The date on which the agency began performance of the role for the monitor.

For the role of reporting, it also indicates the date that precision and accuracy

data applies to the agency as reporting organization.

Attributes: Date

8-digit date Mandatory Coding Instructions: For the role of reporting, begin date is required. Place a valid date string in

the tenth delimited field. A begin date value is valid if it: is in the format of YYYYMMDD, does not fall within any other agency role periods defined for the monitor for the same role name, and falls within a sample period for

the monitor.

5.4.11 End Date

Description: The date on which the agency ended a period of performance of the role for

the monitor. For the role of reporting, it also indicates the last date that precision and accuracy data applies to the agency as reporting organization.

Attributes: Date

8-digit date Mandatory

Coding Instructions: Place a valid date string in the tenth delimited field. An end date value is

valid if it: is in the format of YYYYMMDD, is greater than the begin date, does not fall within any other agency role periods defined for the monitor for the same role name, and falls within a sample period for the monitor.

5.5 MONITORING OBJECTIVE INFORMATION - TRANSACTION TYPE ME

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors. See the data input transaction formats in the Appendices for a list of required fields on each transaction format. For criteria pollutant monitors, transaction types MA through ME are required.

The fields described below are validated for insert (I) and update (U) transactions.

5.5.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

5.5.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

5.5.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

5.5.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

5.5.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing

for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

5.5.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

5.5.7 POC (Parameter Occurrence Code)

Description: An identifier used to distinguish between multiple monitors at the same site

that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple

samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit ID Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

5.5.8 Monitor Objective

Description: Identification of the reason for measuring air quality by the monitor.

Attributes: Alphanumeric

Up to 50 characters

Mandatory

Coding Instructions: Place a valid monitor objective term in the eighth delimited field. A monitor

objective value is valid if it exists in the Monitor Objective Types Table. Multiple monitor objectives, applying to one or more geographical areas, may

be specified.

5.5.9 Urban Area Represented

Description: The urbanized area from which the concentrations originated (not the location

of the monitor).

Attributes: Alphanumeric

4-digit code Optional:

Required on insert Optional on update May not be deleted

Coding Instructions: It is required to designate the origin of concentrations that apply to a monitor

objective classification. One, and only one, of urban area represented, Metropolitan Statistical Area (MSA) represented, or Consolidated Metropolitan Statistical Area (CMSA) represented may be used to indicate the designation. Place a valid urban area represented code in the ninth delimited field. An urban area represented value is valid if it exists in the

Urbanized Areas Table.

5.5.10 MSA Represented

Description: The Metropolitan Statistical Area (MSA) from which the concentrations

originated, not the location of the monitor.

Attributes: Alphanumeric

4-digit code Optional

Coding Instructions: It is required to designate the origin of concentrations that apply to a monitor

objective classification. One, and only one, of urban area represented, MSA represented, or CMSA represented may be used to indicate the designation. Place a valid MSA represented code in the tenth delimited field. An MSA

represented value is valid if it exists in the MSAs Table.

5.5.11 CMSA Represented

Description: The Consolidated Metropolitan Statistical Area (CMSA) from which the

concentrations originated, not the location of the monitor.

Attributes: Alphanumeric

2-digit code Optional

Coding Instructions: It is required to designate the origin of concentrations that apply to a monitor

objective classification. One, and only one, of urban area represented, MSA represented, or CMSA represented may be used to indicate the designation. Place a valid CMSA represented code in the eleventh delimited field. A

CMSA represented value is valid if it exists in the CMSAs Table.

5.6 MONITORING SAMPLING SCHEDULE - TRANSACTION TYPE MF

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors. See the data input transaction formats in the Appendices for a list of required fields on each transaction format. For criteria pollutant monitors, transaction types MA through ME are required.

The fields described below are validated for insert (I) and update (U) transactions.

5.6.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

5.6.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

5.6.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

5.6.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

5.6.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing

for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

5.6.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

5.6.7 POC (Parameter Occurrence Code)

Description: An identifier used to distinguish between multiple monitors at the same site

that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit ID Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

5.6.8 RCF Code

Description: The required collection frequency (RCF) required by either Photochemical

Assessment Monitoring System (PAMS) regulations for organic compounds:

PM-2.5 or PM-10 monitors.

Attributes: Alphanumeric

1- or 2-character code

Mandatory

Coding Instructions: Place a valid RCF code in the eighth delimited field. A RCF code value is

valid if it exists in the Collection Frequencies Table.

5.6.9 RCF Begin Date

Description: The date on which the required collection frequency (RCF) went into effect.

Attributes: Date

8-digit date Mandatory:

Required on insert and update

Prohibited on update if RCF Code blank

May not be deleted

Coding Instructions: Place a valid date string in the ninth delimited field. An RCF begin date

value is valid if it: is in the format of YYYYMMDD, is between July 1, 1987 and one year from the current date, does not fall within any other required collection frequency periods defined for the monitor, and falls within a sample period for the monitor. The RCF begin date cannot be

changed via update.

5.6.10 RCF End Date

Description: The date on which the required collection frequency (RCF) ended.

Attributes: Date

8-digit date Optional

Coding Instructions: Place a valid date string in the tenth delimited field. An RCF end date value

is valid if it: is in the format of YYYYMMDD, is greater than the RCF begin date, is between july 1, 1987 and one year from the current date, does not fall within any other required collection frequency periods defined for the

monitor, and falls within a sample period for the monitor.

5.6.11 Collection Frequency - January to December (12 Instances)

Description: Specifies the collection frequency required within an indicated month for a

monitor's required collection frequency when that frequency is stratified random, random, or seasonal. Twelve slots are available, one for each month

in a year.

Attributes: Numeric

12 digits (nnnnnnnnnn)

Optional

Coding Instructions: The monthly collection frequency is required when the RCF code is 8, 9, or

S (stratified random, random, or seasonal). The delimited field positions for collection frequency are 11-22. Field positions correlate to month number offset by 10, i.e., field 11 is for month 1 (January), field 12 is for month 2 (February), etc. Place a valid collection frequency in the appropriate delimited field. A value is valid if it is a valid collection frequency code for

intermittent sampling (values 1, 2, 3, 4, 5, 6, or 7).

5.7 MONITOR STREET DESCRIPTION - TRANSACTION TYPE MG

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors. See the data input transaction formats in the Appendices for a list of required fields on each transaction format. For criteria pollutant monitors, transaction types MA through ME are required.

The monitor's relationship to nearby streets may be described by using the MG transaction. If either tangent street number or distance from monitor is valued, the other must also be valued. Similarly, one may not be deleted without also deleting the other.

The fields described below are validated for insert (I) and update (U) transactions.

5.7.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

5.7.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

5.7.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

5.7.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

5.7.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to

ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with State code and

county code in the Sites Table.

5.7.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

5.7.7 POC (Parameter Occurrence Code)

Description: An identifier used to distinguish between multiple monitors at the same site

that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple

samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are

reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit ID Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

5.7.8 Tangent Street Number

Description: Designation of a street number that exists for the site. Used to associate

information about the relationship between specific monitors at the site and

tangent roads at the site.

Attributes: Numeric

2 digits (nn) Mandatory

Coding Instructions: Place a valid tangent street number in the eighth delimited field. A tangent

street number is valid if it exists in combination with state code, county code,

and site ID on the Tangent Roads Table.

5.7.9 Distance from Monitor

Description: The distance in meters between the sensing of air sampling equipment at a

monitoring site and the nearest edge of the roadway.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Optional

Coding Instructions: Place a valid distance from monitor value in the ninth delimited field. A

distance from monitor value is valid if it is greater than 0.

5.8 MONITOR OBSTRUCTION INFORMATION - TRANSACTION TYPE MH

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors. See the data input transaction formats in the Appendices for a list of required fields on each transaction format. For criteria pollutant monitors, transaction types MA through ME are required.

The type of obstruction for a monitor with restricted air flow is described by using the MH transaction. See Appendix XX for a description of the transaction formats, including those required to create monitors. For criteria pollutant monitors, transaction types MA through ME are required.

The fields described below are validated for insert (I) and update (U) transactions.

5.8.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

5.8.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

5.8.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

5.8.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

5.8.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether

a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to

ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing for that combination of state ID and county code.

Attributes: Alphanumeric

> 4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

5.8.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

> 5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

5.8.7 POC (Parameter Occurrence Code)

Description: An identifier used to distinguish between multiple monitors at the same site

> that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple

samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit ID Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

5.8.8 Type Obstruction

Description: The type of obstruction responsible for the restricted air flow of a monitor.

Attributes: Alphanumeric

Up to 20 characters

Mandatory

Coding Instructions: Place a valid type obstruction term in the eighth delimited field. A type

obstruction value is valid if it exists in the Probe Obstruction Types Table.

5.8.9 Direction from Monitor

Description: The direction from the monitor to the obstruction.

Attributes: Alphanumeric

3-character code

Mandatory

Coding Instructions: Place a valid direction from monitor in the ninth delimited field. A direction

from monitor value is valid if it exists in the Compass Sectors Table.

5.8.10 Distance to Monitor

Description: The distance, in meters, between the probe and obstruction.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Mandatory

Coding Instructions: Place a valid distance to monitor value in the tenth delimited field. A

distance to monitor value is valid if it is greater than 0.

5.8.11 Height of Obstruction

Description: The height, in meters, of the top of the obstruction above the probe.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Mandatory

Coding Instructions: Place a valid height of obstruction value in the eleventh delimited field. A

height of obstruction value is valid if it is greater than 0.

5.9 MONITOR REGULATORY COMPLIANCE - TRANSACTION TYPE MI

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors. See the data input transaction formats in the Appendices for a list of required fields on each transaction format. For criteria pollutant monitors, transaction types MA through ME are required.

The fields described below are validated for insert (I) and update (U) transactions.

5.9.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

5.9.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

5.9.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

5.9.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

5.9.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing

for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

5.9.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

5.9.7 POC (Parameter Occurrence Code)

Description: An identifier used to distinguish between multiple monitors at the same site

that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit ID Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

5.9.8 Monitor Regulation Code

Description: Identification of an EPA regulation for which compliance documentation is

required.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid monitor regulation code in the eighth delimited field. A

monitor regulation code value is valid if it exists in combination with

parameter on the Parameter Regulations Table.

5.9.9 Compliance Indicator

Description: The compliance status of a monitor with respect to an EPA regulation.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place a compliance indicator in the ninth delimited field. A compliance

indicator value is valid for the following cases: monitor regulation code is RM or ST and compliance indicator is Y or N; monitor regulation code is SC and compliance indicator is Y, N, or W; monitor regulation code is QC and compliance indicator is Y, N, or C. Indicators: Y (in compliance with the regulation), N (not in compliance with the regulation), W (compliance has been waived), or C (in conditional compliance with the regulation).

5.9.10 Compliance Date

Description: The date on which the current status of the monitor's compliance with the

regulation was achieved.

Attributes: Date

8-digit date Mandatory

Coding Instructions:

Place a valid compliance date in the tenth delimited field. A compliance date value is valid if it is in the form of YYYYMMDD and compliance indicator is Y, W, or C.

5.10 MONITOR COLLOCATION PERIOD - TRANSACTION TYPE MJ

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors. See the data input transaction formats in the Appendices for a list of required fields on each transaction format. For criteria pollutant monitors, transaction types MA through ME are required.

The fields described below are validated for insert (I) and update (U) transactions.

5.10.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

5.10.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

5.10.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

5.10.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

5.10.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether

a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing for that combination of state ID and county code.

Attributes: Alphanumeric

> 4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

5.10.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

> 5-digit code Mandatory

Place a valid parameter code in the sixth delimited field. A parameter value Coding Instructions:

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

5.10.7 POC (Parameter Occurrence Code)

An identifier used to distinguish between multiple monitors at the same site Description:

> that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple

samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit ID Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

5.10.8 Collocation Begin Date

Description: The beginning date of the time period during which a collocated monitor pair

recorded precision and accuracy data. Used to determine data completeness.

Attributes: Date

8-digit date Mandatory

Coding Instructions: Place a valid collocation begin date in the eighth delimited field. A

collocation begin date value is valid if:

1) it is in the format of YYYYMMDD, primary monitor indicator is Y, and the collocation begin date does not fall within any other collocation period

defined for the monitor, or

2) primary monitor indicator is N, and collocation begin date falls within a primary monitor collocation period defined for a monitor of the same

parameter at the same site.

5.10.9 Collocation End Date

Description: The ending date of the time period during which a collocated monitor pair

recorded precision and accuracy data. Used to determine data completeness.

Attributes: Date

8-digit date Optional

Coding Instructions: Place a valid collocation end date in the ninth delimited field. A collocation

end date value is valid if:

1) it is in the format of YYYYMMDD and either primary monitor indicator is Y and the collocation end date does not fall within any other collocation

period defined for the monitor, or

2) primary monitor indicator is N, and the collocation end date falls within a primary monitor collocation period defined for a monitor of the same

parameter at the same site.

5.10.10 Distance from Primary Monitor

Description: The distance, in meters, between a duplicate sampler and the primary sampler

in a collocated pair.

Attributes: Numeric

10 digits, including 2 decimal places (nnnnnnn.nn)

Optional

Coding Instructions: Place a valid distance from primary monitor in the tenth delimited field.

5.10.11 Primary Monitor Indicator

Description: Indicates whether the monitor is the primary or duplicate monitor in a

collocated monitor pair.

Attributes: 1-character code: Y or N

Mandatory

Coding Instructions: Place a valid primary monitor indicator in the eleventh delimited field. A

primary monitor indicator value is valid if it is Y (for primary) or N (for not

primary).

5.11 MONITOR PROTOCOL - TRANSACTION TYPE MK

See the transaction requirements in the Appendices for a list of transactions required to create sites and monitors. See the data input transaction formats in the Appendices for a list of required fields on each transaction format. For criteria pollutant monitors, transaction types MA through ME are required.

This transaction is needed only to specify an alternate method detectable limit when the Federal default is not used.

The fields described below are validated for insert (I) and update (U) transactions.

5.11.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

5.11.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

5.11.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

5.11.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

5.11.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

5.11.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

5.11.7 POC (Parameter Occurrence Code)

Description: An identifier used to distinguish between multiple monitors at the same site

that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple

samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit ID

Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

5.11.8 Alternate MP ID

Description: The sequential monitor protocol identification (MP ID) number used to

distinguish combinations of sample duration, unit, method, collection frequency, composite type, and alternate method detectable limit (MDL) for

a monitor.

Attributes: Numeric

4 digits (nnnn) Mandatory

Coding Instructions: Place a valid alternate MP ID in the eighth delimited field. An alternate MP

ID value is valid if it is between 1 and 99 and has not been assigned to

another protocol combination for the monitor.

5.11.9 Sample Duration

Description: The length of time used to acquire raw samples that are analyzed by monitors

and documented in the Raw Data, Precision, or Accuracy Tables. (Formerly:

interval)

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place a valid sample duration code in the ninth delimited field. A sample

duration value is valid if it exists in the Sample Durations Table and if it exists in combination with unit, parameter, method, collection frequency, and

composite type in the Protocols Table.

5.11.10 Unit

Description: The dimensional system in which a pollutant concentration or parameter

reading is expressed.

Attributes: Alphanumeric

3-digit code Mandatory Coding Instructions: Place a valid unit code in the tenth delimited field. A unit value is valid if it

exists in the Units Table and if it exists in combination with sample duration, parameter, method, collection frequency, and composite type in the Protocols

Table.

5.11.11 Method

Description: Specification of a particular method for collecting and analyzing samples of

the monitor's parameter.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid method code in the eleventh delimited field. A method value

is valid if it exists in combination with parameter in the Sampling Methodologies Table, and if it exists in combination with sample duration, unit, collection frequency, and composite type in the Protocols Table.

5.11.12 Collection Frequency

Description: The frequency according to which sample observations are to be made,

specified as the amount of time that elapses between observations. Indicates how often 24-hour samples are taken, e.g., daily, every third day, stratified

random, etc.

Attributes: Alphanumeric

1- or 2-digit code

Optional

Coding Instructions: Place a valid collection frequency code in the twelfth delimited field. A

collection frequency value is valid if it exists in the Collection Frequencies Table and if it exists in combination with parameter, method, sample

duration, unit, and composite type in the Protocols Table.

5.11.13 Composite Type

Description: The time period over which samples are composited, or the frequency of

submitting composite samples.

Attributes: Alphanumeric

10 characters Optional

Coding Instructions: Place a valid composite type term in the thirteenth delimited field. A

composite type value is valid if it exists in the Composite Types Table, it exists in combination with parameter, method, sample duration, unit, and collection frequency in the Protocols Table, and sample duration is C.

5.11.14 Alternate Method Detectable Limit

Description: The method detectable limit defined for the monitor by the reporting agency,

which supercedes the EPA-defined method detectable limit for the designated

methodology.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place an alternate MDL value in the fourteenth delimited field. There are no

edit checks to verify the validity of an alternate method detectable limit value.

5.12 MONITOR COMMENTS (Online Input Only)

Description: Monitor comments is a free-format field that may be used in any way. It is

normally used to describe special features of the monitor.

Attributes: 62-character field

Optional

6.0 RAW DATA TRANSACTIONS (RC, RD)

Transaction Types RC (Composite Raw Data) and RD (Hourly, Daily, and Sub-Hourly Raw Data) perform data manipulation on the Raw Data Table.

The three transactions in this group are used to insert, update, and delete the individual observations of parameter values in the AQS database. Most of the parameter values are the concentrations of air pollutants measured with various methods and at various time intervals. Some non-pollutant observations are also reported, such as wind speed and other meteorological values. Together, these observations of parameter values are collectively called raw data because they are the actual values reported by the monitoring sites.

Simple raw data are the sample values that have been collected by monitoring stations that can be defined for a given date and time of day. Types of simple raw data include: hourly, daily, and subhourly type of data.

Composite data are concentration values derived from two or more air samples obtained at different times and combined and analyzed as one sample.

In contrast to this is the summary data, which is usually calculated from the raw data by the AQS software, and is stored in the Annual Summaries Table (and a few others).

The qualifier field is used only with real observations, when an observed parameter value is present. A non-blank qualifier indicates the observed value is exceptional in some way, usually higher than normal by a substantial amount. The value of the qualifier indicates the cause of the exceptional observation (a forest fire, for example). If no specific cause can be attributed for the exceptional observation, V is coded for the qualifier (to indicate that the value is valid). A non-blank qualifier exempts the associated observation from certain quality assurance qualifiers which it would not otherwise pass. Without the exemption provided by the qualifier, neither the exceptional data nor any normal data for the same day or month would pass the quality assurance qualifiers. If the data failed to pass the qualifiers, it could not be loaded into the AQS database.

Most values do not have qualifiers, since qualifiers are only associated with rare (exceptional) events or circumstances. Furthermore, the use of qualifiers is important only for criteria pollutants. Every episode of qualifier usage (except code V) must be approved by state and EPA officials and must conform with the procedures and requirements set forth in Guideline on the Identification and Use of Air Quality Data Affected by Exceptional Events, publication number EPA-450/4-86-007, July, 1986.

Action codes are interpreted the same way for raw data transactions. Insert actions are used to enter raw data values where none previously existed. The monitor reporting the raw data values must already exist in the AQS Site Table or else there must be valid transactions in the same batch input file to create the monitor. Delete actions are used to remove one or more existing raw data values from the AQS database. Update actions are used to change existing raw data values.

Transaction type RC contains composite raw data in the following fields:

Oualifier-4 Transaction Type Year Action Code Period Qualifier-5 State Code Number of Samples Qualifier-6 Composite Type Qualifier-7 County Code Site ID Sample Value Qualifier-8 Qualifier-9 Parameter Alternate MP ID POC Qualifier-1 Qualifier-10

Unit Qualifier-2 Method Detectable Limit

Method Qualifier-3 Uncertainty

Transaction type RD contains hourly, daily and sub-hourly data in the following fields:

Transaction Type Date Qualifier-5 Action Code Qualifier-6 Start Time Qualifier-7 State Code Sample Value Null Data Code Qualifier-8 County Code Site ID Collection Frequency Qualifier-9 Parameter Alternate MP ID Qualifier-10

POC Qualifier-1 Method Detectable Limit

Sample Duration Qualifier-2 Uncertainty

Unit Qualifier-3 Method Qualifier-4

Detailed coding instructions for these raw data transactions are given in the following sections.

6.1 COMPOSITE RAW DATA - TRANSACTION TYPE RC

See the data input transaction formats in the Appendices for a list of required fields on each transaction format. Transaction type RC is used for composite observations. Type RC transactions insert, update, and delete raw data values in the Raw Data Table of the AQS database.

An insert transaction is used to insert a new observation into the database where none already exists. An update transaction is used to change or delete an existing observation in the database. A delete transaction is used to delete an observation and its associated fields from the database.

6.1.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

6.1.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

6.1.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

6.1.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

6.1.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing

for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

6.1.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

6.1.7 POC (Parameter Occurrence Code)

Description: The code used to distinguish between multiple monitors at the same site that

are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor and it

would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple

samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit code

Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

6.1.8 Unit

Description: The dimensional system in which the pollutant concentration or parameter

reading is expressed.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid unit code in the eighth delimited field. A unit value is valid if

it exists in the Units Table and if it exists in combination with a sample duration of C, parameter, method, and composite type in the Protocols Table.

6.1.9 Method

Description: Identifies a particular method for collecting and analyzing samples of the

monitor's parameter.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid method code in the ninth delimited field. A method value is

valid if it exists in combination with parameter in the Sampling Methodologies Table, and if it exists in combination with the duration code

of C, unit, and composite type in the Protocols Table.

6.1.10 Year

Description: The calendar year for which the observation was reported.

Attributes: Date

4-digit year (yyyy)

Mandatory

Coding Instructions: Place a valid year in the tenth delimited field. A year value is valid if it is in

the form of YYYY, it is between 1957 and the current year, and there is valid

sample period defined for the monitor in that year.

6.1.11 Period

Description: Indicates the time period within the year to which the observation applies.

It is expressed in units that may be inferred from composite type.

Attributes: Alphanumeric

2-digit code Mandatory

Coding Instructions: Place a valid period code in the eleventh delimited field. A period code is

valid if it falls withing the minimum and maximum period defined for

composite type in the Composite Types Table.

Valid period codes depend on composite type as follows:

Сотр Туре	Valid Period Code
1 (Quarterly)	01-04
2 (Seasonal)	01-04
3 (Monthly)	01-12
4 (Weekly)	01-53
5 (Annually)	01

6.1.12 Number of Samples

Description: Indicates the number of samples that were combined to yield the composite

sample value.

Attributes: Alphanumeric

10-digit number Mandatory

Coding Instructions: Place a valid number of samples in the twelfth delimited field. A number of

samples value is valid if it is greater than 0 and is less than the maximum number of samples defined for composite type in the Composite Types Table.

6.1.13 Composite Type

Description: Indicates the time period over which samples are composited or the frequency

of submitting composite samples.

Attributes: Alphanumeric

10 characters Optional

Coding Instructions: Place a valid composite type term in the thirteenth delimited field. A

composite type value is valid if it exists in the Composite Types Table, it exists in combination with parameter, method, sample duration equal to C,

and unit in the Protocols Table.

6.1.14 Sample Value

Description: The value of a composite observation.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Mandatory

Coding Instructions: Place the sample value in the thirteenth delimited field. Reported scale is

implied from the number of digits allocated to the right of the decimal point. For example, to submit the value of 1.2 in the scale of 3, then submit the

value as 1.200.

For some parameters, upper and lower limits have been established for observations. The sample value is compared to these limits, if they exist on the Parameters Table for the pollutant. If the sample value falls outside the range defined by the absolute max sample value and the absolute min sample value, and there is no qualifier entered with the sample value, then the sample value will be rejected with an error message.

Lead (12128) is the only parameter that is reported as a composite observation (duration code = C), and that has an absolute maximum sample value defined on the Parameters Table. The relevant maximum values for lead composite observations are listed below:

Para- meter	Code	Units	Abs Max Sample Value	Abs Min Sample Value	Fed Rel Max Sample Value	Fed Rel Min Sample Value
Lead	12128	μg/m³ (25 C)	200	0	100	0

If the sample falls outside the range defined by the Federal relative maximum sample value and Federal relative minimum sample value, and there is not qualifier entered with the sample value, then the sample will not be rejected, but will be highlighted in the Statistical Critical Review Report with a warning message.

6.1.15 Alternate MP ID

Description: The sequential monitor protocol identification (MP ID) number used to

distinguish combinations of sample duration, unit, method, collection frequency, composite type, and alternate method detectable limit (MDL) for

a monitor.

Attributes: Numeric

2 digits (nn) Optional

Coding Instructions: Place a valid alternate MP ID number in the fifteenth delimited field. An

alternate MP ID value is valid if it exists in the monitor Protocols Table for the monitor. (Note: it is only necessary to provide this value if an alternate MDL applies to the sample value; otherwise, the appropriate monitor protocols can be derived.) If an MP ID does not exist for the combination of codes, but the combination exists on the Protocols Table, a new MP ID will

be assigned.

6.1.16 Qualifier 1-10

Description: Qualifications used to describe the composite raw data. They may document

exceptional data or quality assurance exceptions.

Attributes: Alphanumeric

1- or 2-character code

Optional

Coding Instructions: Ten fields (delimited fields 16-25), are allocated for the designation of

composite data qualifiers. It is valid to designate one, and only one, exceptional data qualifier, and as many quality assurance qualifiers as are necessary. To designate qualifiers, use the available fields in sequence: place the first qualification in field 16, the second in field 17, and so on. A

particular qualifier value is valid if it exists in the Qualifiers Table.

6.1.17 Method Detectable Limit

Description: Method detectable limit (MDL) is the minimum detectable level defined for

the monitor and method.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place a valid MDL in the 26th delimited field. A user can report MDL on the

composite raw data (RC) transaction, or leave it blank. If it is reported on the composite raw data transactions, then the software looks to see whether it is a new MDL value (i.e., does not exist on the Monitor Protocol Table). If it is a new value, a new monitor protocol record is system-generated and that new monitor protocol identification (MP ID) number is stored with the raw data value.

If the reported MDL value is not a new value, and there is already a monitor protocol record for that method and MDL, then the existing alternate MP ID from the Monitor Protocol Table is stored with the raw data value.

Another way of reporting a new MDL is to create a new monitor protocol with the new value using the MK transaction. Then the raw data transactions can reference the new monitor protocol record being created in the batch stream, and the MDL value is not needed, since it is already on the protocol record. To do this, the alternate MP ID on the MK record being created would be the same value contained in the alternate MP ID field on the RC or RD transactions.

6.1.18 Uncertainty

Description:

Attributes: Numeric

10 digits, including 5 decimal places (nnnn.nnnnn)

Coding Instructions:

6.2 HOURLY, DAILY, AND SUB-HOURLY RAW DATA - TRANSACTION TYPE RD

The type RD transaction is used for parameter observations with sampling intervals less than or equal to 24 hours. See the data input transaction formats in the Appendices for a list of required fields on each transaction format.

An insert transaction is used to insert observations or qualifiers into the database where neither currently exists. An update transaction is used to change or delete existing observations or missing value reason codes. A delete transaction is used to remove all the existing observations and missing value reason codes within the temporal scope of the transaction.

6.2.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

6.2.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

ables.

D - Delete a row from a table(s) for the row containing the key data.

6.2.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

6.2.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

6.2.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

6.2.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

6.2.7 POC (Parameter Occurrence Code)

Description: An identifier used to distinguish between multiple monitors at the same site

that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple

samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit ID Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

6.2.8 Sample Duration

Description: The period of time during which the raw sample value was collected.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place a valid sample duration code in the eighth delimited field. A sample

duration value is valid if it exists in the Sample Durations Table and if it exists in combination with unit, parameter, method, and collection frequency

in the Protocols Table.

6.2.9 Unit

Description: The dimensional system in which the pollutant concentration or parameter

reading is expressed.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid unit code in the ninth delimited field. A unit value is valid if it

exists in the Units Table and if it exists in combination with parameter, sampling duration, method, and collection frequency in the Protocols Table.

6.2.10 Method

Description: Identifies a particular method for collecting and analyzing samples of the

monitor's parameter.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid method code in the tenth delimited field. A method code is

valid if it exists in combination with parameter in the Sampling Methodologies Table, and if it exists in combination with parameter,

sampling duration, units, and collection frequency in the Protocols Table.

6.2.11 Date

Description: The calendar date for which the observation is being reported.

Attributes: Date

8-digit date Mandatory

Coding Instructions: Place a valid date in the eleventh delimited field. A date value is valid if it

is in the form of YYYYMMDD, it is between 1957 and the current year, and

it falls within a valid sample period defined for the monitor.

6.2.12 Start Time

Description: Indicates the beginning of the sampling period in standard time at the location

of the monitoring site.

Attributes: Alphanumeric

5 characters Mandatory

Coding Instructions: Place a valid start time in the twelfth delimited field. A start time value is

valid if it is in the format of HH:MM, and does not overlap another sampling

period for the monitor.

6.2.13 Sample Value

Description: The value of an observation being reported.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place the sample value in the thirteenth delimited field. Reported scale is

implied from the number of digits allocated to the right of the decimal point. For example, to submit the value of 1.2 in the scale of 3, then submit the

value as 1.200.

For some parameters, upper and lower limits have been established for observations. The sample value is compared to these limits, if they exist on the Parameters Table for the pollutant. If the sample value falls outside the range defined by the absolute max sample value and the absolute min sample

value, and there is no qualifier entered with the sample value, then the sample value will be rejected with an error message.

If the sample falls outside the range defined by the Federal relative maximum sample value and Federal relative minimum sample value, and there is not qualifier entered with the sample value, then the sample will not be rejected, but will be highlighted in the Statistical Critical Review Report with a warning message.

The relevant maximum values and parameters are listed below:

Para- meter Code	Parameter Description	Abs Max Sample Value	Abs Min Sample Value	Fed Rel Max Sample Value	Fed Rel Min Sample Value	Unit
11101	Suspended Particulate (TSP)	10000	0	1000	0	μg/meter³ (25 c)
12128	Lead (TSP)	200	0	100	0	μg/meter³ (25 c)
42101	Carbon Monoxide	150	0	75	0	parts per million (ppm)
42401	Sulfur Dioxide	5	0	1	0	ppm
42601	Nitric Oxide	5	0	1	0	ppm
42602	Nitrogen Dioxide	3	0	1	0	ppm
42603	Oxides of Nitrogen	5	0	1.5	0	ppm
43101	Total Hydro- carbons	99999	0	10000	0	parts per billion carbon
43102	Total NMOC	20000	0	10000	0	parts per billion carbon
43201	Methane	99999	0			parts per billion carbon
44201	Ozone	0.7	0	0.4	0	pm
61102	Wind Direction	360	0	360	0	degrees, compass
61104	Resultant Direction	360	0	360	0	degrees, compass
61106	Std Dev Hz Wind Dir	360	0	360	0	degrees, compass

Para- meter Code	Parameter Description	Abs Max Sample Value	Abs Min Sample Value	Fed Rel Max Sample Value	Fed Rel Min Sample Value	Unit
61107	Std Dev Vt Wind Dir	360	0	360	0	degrees, compass
61112	Vert Wind Direction	360	0	360	0	degrees, compass
62101	Outdoor Temperature	150	-60			degrees, Fahrenheit
62102	Virtual Temperature	150	-60			degrees, Fahrenheit
62104	Temperature 24-Hour Max	150	-60			degrees, Fahrenheit
62105	Temperature 24-Hour Min	150	-60			degrees, Fahrenheit
62107	Indoor Temperature	150	-60			degrees, Fahrenheit
62201	Relative Humidity	100	0			percent rel humidity
68101	Sample Flow Rate - CV	20	0	20	0	percent
68102	Sample Volume	25.2	8			cubic meter
68103	Ambient Min Temperature	55	-40	55	-40	degrees, centigrade
68104	Ambient Max Temperature	55	-40	55	-40	degrees, centigrade
68105	Ambient Avg Temperature	55	-40	55	-40	degrees, centigrade
68106	Sample Min Barometric Pressure	850	450	850	450	millimeters (mercury)
68107	Sample Max Barometric Pressure	850	450	850	450	millimeters (mercury)
68108	Sample Avg Barometric Pressure	850	450	850	450	millimeters (mercury)
68109	Elapsed Sample Time	1500	480			minutes
81102	PM-10 Total 0-10 Um	5000	-10	500	-10	μg/cubic meter (25 c)
88101	PM-2.5 Local Conditions	5000	-10	500	-10	μg/cubic meter (LC)

6.2.14 Null Data Code

Description: Code to explain why no sample value was reported.

Attributes: Alphanumeric

2-character code

Optional

Coding Instructions: Place a valid null value code in the fourteenth delimited field. A null data

code value is valid if it exists in the Qualifiers Table with the qualifier type

of null.

6.2.15 Collection Frequency

Description: Indicates the elapsed time period between observations.

Attributes: Alphanumeric

1- or 2-digit code

Optional

Coding Instructions: Place a valid collection frequency code in the fifteenth delimited field. A

collection frequency is required only for PM-10 and PM-2.5. For hourly data, leave collection frequency blank. A collection frequency value is valid if it exists in the Collection Frequencies Table, and if it exists in combination with parameter, method, sample duration, and unit in the Protocols Table.

6.2.16 Alternate MP ID

Description: The sequential monitor protocol identification (MP ID) number used to

distinguish combinations of sample duration, unit, method, collection frequency, composite type, and alternate method detectable limit (MDL) for

a monitor.

Attributes: Numeric

2 digits (nn) Optional

Coding Instructions: Place a valid alternate MP ID number in the sixteenth delimited field. An

alternate MP ID value is valid if the MP ID Value exists in the monitor Protocols Table for the monitor. (Note: it is only necessary to provide this value if an alternate MDL applies to the sample value; otherwise, the

appropriate monitor protocols can be derived.)

6.2.17 Qualifier 1-10

Description: Qualifications used to describe the composite raw data. They may document

exceptional data, or quality assurance exceptions.

Attributes: Alphanumeric

1- or 2-character code

Optional

Coding Instructions: Ten fields (delimited fields 17-26), are allocated for the designation of raw

data qualifiers. It is valid to designate one, and only one, exceptional data qualifier, and as many quality assurance qualifiers as are necessary. To designate qualifiers, use the available fields in sequence: place the first qualification in field 17, the second in field 18, and so on. A particular

qualifier value is valid if it exists in the Qualifiers Table.

6.2.18 Method Detectable Limit

Description: Method detectable limit (MDL) is the minimum detectable level defined for

the monitor and method.

Attributes: Numeric

10 digits, including 5 decimal places (nnnn.nnnn)

Optional

Coding Instructions: Place a valid MDL in the 27th delimited field. A user can report MDL on the

hourly, daily and sub-hourly raw data (RD) transaction, or leave it blank. If it is reported on the raw data transactions, then the software looks to see whether it is a new MDL value (i.e., does not exist on the Monitor Protocol Table). If it is a new value, a new monitor protocol record is system-generated and that new monitor protocol identification (MP ID) number is

stored with the raw data value.

If the reported MDL value is not a new value, and there is already a monitor protocol record for that method and MDL, then the existing alternate MP ID

from the Monitor Protocol Table is stored with the raw data value.

Another way of reporting a new MDL is to create a new monitor protocol with the new value using the MK transaction. Then the raw data transactions can reference the new monitor protocol record being created in the batch stream, and the MDL value is not needed, since it is already on the protocol record. To do this, the alternate MP ID on the MK record being created would be the same value contained in the alternate MP ID field on the RC or RD transactions.

6.2.19 Uncertainty

Description:

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Coding Instructions:

6.3 STATISTICAL TESTS

The pattern and gap tests performed on hourly data (duration of 1) are described briefly below. See EPA document Screening Procedures for Ambient Air Quality for more detailed information (publication # EPA-450/2-78-037, July 1978). The values are validated via the following statistical tests, and results are included in the Statistical Critical Review Report for user review prior to posting as production data.

6.3.1 Pattern Tests

Pattern tests are performed on hourly data for pollutants 44201 ozone (O_3) , 42101 carbon monoxide (CO), 42401 sulfur dioxide (SO_2) , and 42602 nitrogen dioxide (NO_2) . Exceptional event data are excluded from the tests. The tests are run on a month of hourly data. Essentially, each test scans the month's values and compares them against empirically derived thresholds to determine if they are questionable. If so, the value is flagged as failing that particular test. The raw data values are converted to the appropriate units before the tests are applied. The factors used to convert from reporting units to the units of the tests are given in Table 6-1. The threshold values for each pollutant and each test are listed in Table 6-2. As that Table shows, different threshold values pertain depending on the season of the year and the time of day.

The Dixon test (not applied to CO) scans each day's values and determines the highest, second highest, and lowest values in that day. It then computes the Dixon ratio, defined as (max - secmax)/(max -low). If this value is greater than 0.55, the day fails the Dixon test and all hours are marked as failing.

The max hour test compares each value in the month to a constant to determine if the value is too high. If so, it is marked as failing.

The high difference test compares the value at each hour in the month to the previous hour and the subsequent hour. If the difference between any two hours is greater than allowable, then the hour under inspection is marked as failing.

The spike test works much like the high difference test, except that both differences must be greater than allowable for the test to fail. Also, the percentage difference between the hour in question and both its adjacent hours must be greater than allowable for the test to fail. If either the difference or the percentage comparison fails, the value is rejected.

The high consecutive values test looks at each hour and the subsequent three hours. If all four values are greater than allowable, then all four hours are marked as failing the test.

Table 6-1 Conversion Factors for the Pattern and Gap Tests

Pollutant	Units for Gap and Pattern Tests	Reported Units	Conversion Factors	
42101 (CO)	42101 (CO) parts per million (ppm)		0.86957 0.79653 1.0 0.001	
42401 (SO ₂)	pphm*	001 (µg/m³ 25°) 002 (µg/m³ 0°) 007 (ppm) 008 (ppb)	0.03817 0.03496 100.0 0.1	
42602 (NO ₂)	pphm*	001 (µg/m³ 25°) 002 (µg/m³ 0°) 007 (ppm) 008 (ppb)	0.05319 0.04872 100.0 0.1	
44201 (O ₃)	44201 (O ₃) pphm*		0.05102 0.04673 100.0 0.1	

^{*}ppm - parts per million, mg/m³ - milligrams per cubic meter, ppb - parts per billion, pphm - parts per hundred million, μ g/m³ - micrograms per cubic meter

Table 6-2 Threshold Values for the Pattern Tests

Pollutant	Data Minimum Stratification	Maximum Hour Test	High Difference Test	Spike	Consecutive Values Test	Value*
Ozone (pphm)	Summer-Day Months: 05-10 Hours: 10-17	50	15	10 (300%)	26	5
	Summer-Night Months: 05-10 Hours: 18-09	38	10	5 (300%)	26	5
	Winter-Day Months: 11-04 Hours: 10-17	26	13	10 (300%)	26	5
	Winter-Night Months: 11-04 Hours: 18-09	15	10	5 (300%)	26	5
Carbon Monoxide (ppm)	Rush Traffic Hours: 06-10 06-20	65	22	17 (500%)	35	17
	Non-Rush Traffic Hours: 11-15 21-05	44	22	17 (500%)	35	17
Sulfur Dioxide	Zone 1 Regions 1, 5, 6, 7	99	19	8 (500%)	38	25
(pphm)	Zone 2 Regions 2, 3, 4	50	11	8 (500%)	38	25
	Zone 3 Regions 8, 9, 10	30	8	8 (500%)	38	25
Nitrogen Dioxide (pphm)	None	64	27	11 (300%)	53	12

^{*}Values below the minimum are excluded from the high difference and spike tests.

6.3.2 Gap Test

The gap test is performed on data for pollutants 44201 (O₃), 42101 (CO), 42401 (SO₂), and 42602 (NO₂). Exceptional events data are excluded. The gap test is so named because it looks for gaps in the Frequency Distribution Table for a month's values. The test is run on a month of hourly data (duration of 1). For each pollutant, the program builds a Frequency Distribution Table and computes constants associated with the frequency distribution. If there is not enough data to compute the constants, a warning is issued. Having determined the constants, a largest reasonable gap is estimated. Then the largest actual gap in the data is determined and compared to the largest estimated gap to determine whether the month passes or fails the gap test.

6.3.3 Patterns and Gap Failure Report

The patterns and gap failure report is produced by the Critical Review (CR) statistics program. The report identifies the day in which a pattern test failed or the month in which the gap test failed, and it shows the first and last keys of the transactions involved in the failed test. Under the heading hourly values failing test(s)/test(s) failed, the report gives additional information to help identify the values that failed the test.

For pattern test failures, the report shows all the values for each day in which a value failed a test. If database values are being changed with update transactions, some of the values listed may be from the database and some from the transactions in the batch transaction file. One-letter codes under the values indicate which of the pattern tests a value failed. If a particular value failed more than one test, multiple codes are listed. The codes are:

- C High consecutive values test
- D Dixon test
- H High difference test
- M Max hour test
- S Spike test

The codes are also listed on each page of the reports as part of the page heading.

Determining which values are involved in a failure of the gap test is a bit more difficult. The gap test identifies a gap in the frequency distribution of a month's values. Often, but not always, the gap is due to an outlier, a value unusually higher or lower than the bulk of the data for the month. The patterns and gap failure report does not identify the date and hour of the value(s) failing the gap test, but it does give information that may allow manual identification of the values(s). Gap size is the difference in magnitude between the two values on either side of the gap in the frequency distribution, expressed in the units used for the gap test (ppm or pphm). Num above gap is the number of values above the gap. If the number of values is large, the gap is in the smallest values for the month. Finally, slot below gap is the value on the low end of the gap, expressed in the units of the test (ppm or pphm).

6.3.4 Shewhart Test

The Shewhart test which is performed on daily data is described briefly herein. See EPA Document Screening Procedures for Ambient Air Quality for more detailed information (publication # EPA-450/2-78-037, July 1987).

The Shewhart test is performed on daily data (duration is 7, 24-hour) for pollutants 12128 (Pb), 42401 (SO₂), 42602 (NO₂), 88101 (PM-2.5), and 81102 (PM-10). Exceptional events data are excluded. The test is run on a month of daily data. The program counts the number of valid samples for the current month and each of the three previous months. If there is insufficient data to perform the test, a warning message is issued. Given sufficient data for at least two of the three previous months, the program computes the mean and range for the current month. It then computes the historical mean and range, from the mean and range of the data for the three historical months. The mean and range for the current month are compared against the historical values to determine whether the current month passes or fails the Shewhart test.

7.0 ACCURACY/PRECISION TRANSACTIONS (RA, RP)

The two transactions in this group are used to insert, update, and delete the individual observations of parameter values in the AQS database, for accuracy and precision data. The parameter values are the known and observed concentrations of air pollutants measured with the various methods and at various time intervals. These observations of parameter values are collectively called raw accuracy/precision data because they are the actual, unprocessed values reported by the monitoring sites. This is contrasted with the summaries of the observations derived by AQS software.

In the accuracy/precision Raw Data Tables, there are two sets of fields for each possible observation: actual value, which is the known concentration of a parameter, and indicated value, which is the observed concentration of a parameter as measured by the monitor.

Action codes are interpreted the same way for both types of accuracy/precision raw data transactions: Insert actions are used to enter accuracy/precision raw data values where none previously existed. The monitor reporting the accuracy/precision raw data values must already exist in the database. Delete actions are used to remove one or more existing accuracy/precision raw data values from the AQS database. Update actions are used to change existing accuracy/precision raw data values.

The two types of accuracy/precision raw data transactions have several fields in common: transaction type, action code, state code, country code, site ID, parameter, POC, and unit.

Transaction type RA contains accuracy data in the following fields:

Transaction Type Year Represented Level 1 Indicated Value Quarter Represented Action Code Level 2 Actual Value State Code Level 2 Indicated Value Date Level 3 Actual Value County Code Type Audit Site ID Local Primary Standard Level 3 Indicated Value Parameter **Audit Class** Level 4 Actual Value **POC** Accuracy Type Level 4 Indicated Value Audit Sample ID Other Level Actual Value Accuracy Audit ID Number Sample Duration **Expiration Date** Other Level Indicated Value Unit Audit Scheduled Zero Span

Method Level 1 Actual Value

Transaction type RP contains precision data in the following fields:

POC Actual Value Transaction Type Action Code Precision ID Indicated Method Sample Duration Indicated Value State Code County Code Collocated POC ID Unit Site ID Actual Method Precision Sample ID Agency Performing Audit Parameter Date

Detailed coding instructions for the common fields and for the two accuracy/precision transactions are given below.

7.1 ACCURACY DATA - TRANSACTION TYPE RA

The type RA transaction is used for parameter observations at various intervals to insert, update, or delete accuracy raw data values.

For intermittent monitors, the actual value is the known value from the audit device. The indicated value is the observation recorded by the sampler.

For continuous monitors, the actual value is the known concentration of the gas mixture used to challenge the monitor. The indicated value is the observed concentration of gas indicated when the monitor was challenged with a known concentration of gas mixture. For continuous PM monitors, the actual value is the known value for the audit device, and the indicated value is the value observed by the sampler.

An insert transaction is used to insert observations into the database. An update transaction is used to change existing observations. A delete transaction is used to remove existing observations.

7.1.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

7.1.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

7.1.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

7.1.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

7.1.5 Site ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether

a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to

ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

7.1.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

7.1.7 POC (Parameter Occurrence Code)

Description: An identifier used to distinguish between multiple monitors at the same site

that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple

samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a

different POC.

Attributes: Numeric

2-digit ID Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

7.1.8 Accuracy Audit ID Number

Description: A sequentially assigned number used to identify (ID) a unique measurement

data group for a monitor on a specific date.

Attributes: Numeric

1-digit code (n)

Mandatory when using the new transaction format (pipe-delimited)

Optional when using the old transaction format (80 columns) and reporting only one audit transaction for the day. If more than one audit is performed on the same day, then this field must be valued for each accuracy transaction

for that day, with different values to keep the transactions unique.

Coding Instructions: Place a valid accuracy audit ID number in the eighth delimited field. Valid

values are 1 through 5.

For the old transaction format (80 columns): This ID is mandatory in the database, but not mandatory on the old format transactions. If left blank, the system will generate a ID of 1 for the transaction on the load step. However, if you are submitting multiple accuracy transactions for the same monitor and day, be sure to supply unique accuracy audit ID numbers for each transaction. This applies to the

old transaction format only.

For the new transaction format (pipe-delimited), the accuracy audit ID

number must always be supplied.

7.1.9 Sample Duration

Description: The period of time during which the raw sample value was collected.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place a valid sample duration code in the ninth delimited field. A sample

duration value is valid if it exists in the Sample Durations Table and if it exists in combination with unit, parameter, method, and collection frequency

in the Protocols Table.

7.1.10 Unit

Description: The dimensional system in which the pollutant concentration or parameter

reading is expressed.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid unit code in the tenth delimited field. A unit value is valid if it

exists in the Units Table, and if it exists in combination with parameter, sampling duration, method, and collection frequency in the Protocols Table.

7.1.11 Method

Description: Identifies a particular method for collecting and analyzing samples of the

monitor's parameter.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid method code in the eleventh delimited field. A method code

value is valid if it exists in combination with parameter in the Sampling Methodologies Table, and if it exists in combination with the parameter,

sampling duration, and unit in the Protocols Table.

7.1.12 Year Represented

Description: The year represented by the audit.

Attributes: Date

4-digit year (yyyy)

Optional

Coding Instructions: Place a valid year represented number in the twelfth delimited field. A year

represented value is valid if it is in the format of YYYY and is less than or equal to accuracy date's year. The year represented is required only for lead analytical audits performed in the laboratory, to link the year to the

concentration samples analyzed during the audits.

7.1.13 Quarter Represented

Description: The quarter represented by the audit.

Attributes: Alphanumeric

2 characters

Optional

Coding Instructions: Place a valid quarter represented number in the thirteenth delimited field. A

quarter represented value is valid if it is Q1, Q2, Q3, or Q4, and is less than or equal to the quarter of the analysis, or any quarter of the previous year. The quarter represented is required only for lead (Pb) analytical audits performed in the laboratory, to link the quarter to the concentration samples

analyzed during the audits.

7.1.14 Date

Description: The calendar date for which the accuracy audit is being reported.

Attributes: Date

8-digit date Mandatory

Coding Instructions: Place a valid date in the fourteenth delimited field. A date value is valid if:

It is in the form of YYYYMMDD,

It is between January 1, 1980 and the current date,

It falls within a valid sample period defined for the monitor, and, If a criteria pollutant monitor is being audited, it falls within a valid

reporting organization period.

7.1.15 Type Audit

Description: Description of who performed the audit and how the audit standard was

certified.

Attributes: Alphanumeric

20 characters Mandatory

Coding Instructions: Place a valid type audit term in the fifteenth delimited field. A type audit

value is valid if it exists in the Audit Types Table.

7.1.16 Local Primary Standard

Description: The source of the local primary standards used for the audit.

Attributes: Alphanumeric

30 characters Mandatory

Coding Instructions: Place a valid local primary standard term in the sixteenth delimited field. A

local primary standard term is valid if it exists in the Local Primary Standards

Table.

7.1.17 Audit Class

Description: Description of the class of audit taken at the monitor.

Attributes: Alphanumeric

20 characters Mandatory

Coding Instructions: Place a valid audit class term in the seventeenth delimited field. An audit

class term is valid if it exists in the Audit Classes Table, and, if there is an entry in the protocol Audit Classes Table for the parameter, sample duration, and unit combination, it matches the prescribed audit class term for that

combination.

Values are Analytical, Flow, and Span.

Please note that, for the parameter-interval-units combination indicated in the following table, an audit class of Analytical is always required.

Parameter	Interval	Units	Audit Class
12128	7, 8, C	077	Analytical

7.1.18 Accuracy Type

Description: A description of the type of accuracy test performed.

Attributes: Alphanumeric

20 characters Mandatory

Coding Instructions: Place a valid accuracy type term in the eighteenth delimited field. An

accuracy type term is valid if it exists in the Accuracy Types Table.

7.1.19 Audit Sample ID

Description: The unique identity (ID) number of the reference sample used to challenge

the instrument.

Attributes: Alphanumeric

10 characters Optional

Coding Instructions: Place the audit sample ID alphanumeric text in the nineteenth delimited field.

No edit checks are performed on an audit sample ID value.

7.1.20 Expiration Date

Description: The expiration date for the local primary standard.

Attributes: Date

> 8-digit date **Optional**

Coding Instructions: Place a valid expiration date in the twentieth delimited field. An expiration

date value is valid if it is in the format of YYYYMMDD.

7.1.21 Audit Scheduled

The initial date that the performance audit was scheduled. Description:

Attributes: Alphanumeric

> 8 characters **Optional**

Coding Instructions: Place a valid audit scheduled date in the twenty-first delimited field. An

audit scheduled value is valid if it is in the format of YYYYMMDD.

7.1.22 Level 1-4 Actual Value

Description: The true observation of the parameter value at the prescribed audit level.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: The accuracy data transaction format allows for the specification of actual

> values for four levels. The levels are position-dependent and coordinate with the audit levels defined for the parameter and the method's recording mode (continuous or intermittent) in the Audit Levels Table. Each actual value must be submitted with a corresponding indicated value for the same level. The level 1 actual value is assigned to the twenty-second delimited field; level 2, to the twenty-fourth; level 3 to the twenty-sixth; level 4, to the twenty-eighth. Place the true values of parameter concentrations being used to challenge the monitor according to the defined levels in the appropriate field. An actual value is valid if it falls within the corresponding range of values defined for the parameter and recording mode in the Audit Levels Table. If no range is defined for the level, than the value is considered to be valid, but is not included in data completeness determinations.

For some parameters, a range of expected values has been established for observations. Concentrations reported outside the range may be data for another audit level. The relevant ranges and parameters are listed below. Ranges are specified in 40 Code of Federal Regulations (CFR) Park 58 Appendix A. The ranges included in AQS, however, have been expanded to allow data entry.

Parameter Code	Parameter Description	Level Number	Range
12128	Lead (TSP)	1	0.5 - 2.5 μg/m³ (25 c)
12128	Lead (TSP)	2	2 - 5 μg/m³ (25 c)
42101	Carbon Monoxide	1	2.7 - 10.5 ppm
42101	Carbon Monoxide	2	13.5 - 22 ppm
42101	Carbon Monoxide	3	21.1 - 49.5 ppm
42101	Carbon Monoxide	4	72 - 99 ppm
42401	Sulfur Dioxide	1	0.027 - 0.095 ppm
42401	Sulfur Dioxide	2	0.135 - 0.31 ppm
42401	Sulfur Dioxide	3	0.221 - 0.495 ppm
42401	Sulfur Dioxide	4	0.72 - 0.99 ppm
42602	Nitrogen Dioxide	1	0.027 - 0.088 ppm
42602	Nitrogen Dioxide	2	0.135 - 0.22 ppm
42602	Nitrogen Dioxide	3	0.221 - 0.51 ppm
42602	Nitrogen Dioxide	4	0.72 - 0.99 ppm
44201	Ozone	1	0.027 - 0.09 ppm
44201	Ozone	2	0.135 - 0.26 ppm
44201	Ozone	3	0.22 - 0.495 ppm
44201	Ozone	4	0.72 - 0.99 ppm

For some parameters, percent differences are utilized to reject data that could be in error as a result of transcription errors. The maximum percent differences and parameters are listed below:

Parameter Code	Maximum Percent Difference
44201	<u>+</u> 90 %
42602	<u>+</u> 90 %
42401	<u>+</u> 90 %
42101	<u>+</u> 90 %
12128	<u>+</u> 90 %

The percent difference is calculated using the following formula:

$$\frac{\cancel{(indicated - actual)}}{actual} \times 100$$

7.1.23 Level 1-4 Indicated Value

Description: The recorded observation of the parameter value at the prescribed audit level.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions:

The accuracy data transaction format allows for the specification of indicated values for four levels. The levels are position-dependent and coordinate with the audit levels defined for the parameter and the method's recording mode (continuous or intermittent) in the Audit Levels Table. Each indicated value must be submitted with a corresponding actual value for the same level. The level 1 indicated value is assigned to the twenty-third delimited field; level 2, to the twenty-fifth; level 3 to the twenty-seventh; level 4, to the twenty-ninth. Place the recorded values of parameter concentrations that were used to challenge the monitor according to the defined levels in the appropriate field. An indicated value is valid if its percentage difference relative to the actual value does not exceed the level defined for the parameter on the Parameters Table.

For some parameters, a range of expected values has been established for observations. Concentrations reported outside the range may be data for another audit level. The relevant ranges and parameters are listed below. Ranges are specified in 40 CFR Park 58 Appendix A. The ranges included in AQS, however, have been expanded to allow data entry.

Parameter Code	Parameter Description	Level Number	Range
12128	Lead (TSP)	1	0.5 - 2.5 μg/cubicmeter (25 c)
12128	Lead (TSP)	2	2 - 5 μg/cubicmeter (25 c)
42101	Carbon Monoxide	1	2.7 - 10.5 ppm
42101	Carbon Monoxide	2	13.5 - 22 ppm
42101	Carbon Monoxide	3	21.1 - 49.5 ppm
42101	Carbon Monoxide	4	72 - 99 ppm
42401	Sulfur Dioxide	1	0.027 - 0.095 ppm
42401	Sulfur Dioxide	2	0.135 - 0.31 ppm
42401	Sulfur Dioxide	3	0.221 - 0.495 ppm
42401	Sulfur Dioxide	4	0.72 - 0.99 ppm

Parameter Code	Parameter Description	Level Number	Range
42602	Nitrogen Dioxide	1	0.027 - 0.088 ppm
42602	Nitrogen Dioxide	2	0.135 - 0.22 ppm
42602	Nitrogen Dioxide	3	0.221 - 0.51 ppm
42602	Nitrogen Dioxide	4	0.72 - 0.99 ppm
44201	Ozone	1	0.027 - 0.09 ppm
44201	Ozone	2	0.135 - 0.26 ppm
44201	Ozone	3	0.22 - 0.495 ppm
44201	Ozone	4	0.72 - 0.99 ppm

For some parameters, percent differences are utilized to reject data that could be in error as a result of transcription errors. The maximum percent differences and parameters are listed below:

Parameter Code	Maximum Percent Difference
44201	<u>+</u> 90 %
42602	<u>+</u> 90 %
42401	<u>+</u> 90 %
42101	<u>+</u> 90 %
12128	<u>+</u> 90 %

The percent difference is calculated using the following formula:

$$\frac{\underbrace{\textit{(indicated - actual)}}}{\textit{actual}} \times 100$$

7.1.24 Other Level Actual Value

Description: The true observation of the parameter value at a user-defined level.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: The accuracy data transaction format allows for the specification of an

accuracy audit pair not tied to the audit levels defined for the parameter and recording mode. Place the actual value of the pair in the thirtieth delimited

field.

7.1.25 Other Level Indicated Value

Description: The reported observation of the parameter value at a user-defined level.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: The accuracy data transaction format allows for the specification of an

accuracy audit pair not tied to the audit levels defined for the parameter and recording mode. Place the indicated value of the pair in the thirty-first

delimited field.

7.1.26 Zero Span

Description: A measurement obtained with gas from a zero concentration. Zero span is

the observed value read from the instrument when the concentration of the

specific parameter used to test the monitor was zero.

Attributes: Numeric

10 digits, including 5 decimals (nnnn.nnnn)

Optional

Coding Instructions: Place the zero span value in the thirty-second delimited field.

7.2 PRECISION DATA - TRANSACTION TYPE RP

The type RP transaction is used for reporting quality control information. The values reported by intermittent collocated monitors are checked for agreement among the collocated monitors. Continuous monitors are challenged with a known concentration of gas. See Section 7.0 for a list of fields on the RP transaction.

An insert transaction is used to insert an observation into the database where it does not currently exist.

An update transaction is used to change or delete existing observations. The actual method and actual value fields on this transaction pertain to the designated monitor, and the indicated method and indicated value fields pertain to the collocated sampler (monitor). For continuous monitors, the indicated method and indicated value fields pertain to a known gas mixture.

If both the indicated and actual values from the intermittent collocated samplers are reported to the raw data files, then only the monitor ID (State-County-Site-Parameter-POC) and the collocated POC ID are required on the RP transaction, along with the date.

In other words, precision data from collocated monitors can be submitted in two different ways:

- 1) One way is to include the actual and indicated values on the precision transaction. In this case, there must be a daily raw data observation value in the database for the primary monitor, and this value must match the actual value on the precision transaction. If there is a raw data observation for the collocated POC ID, then the value supplied for indicated value must match that raw data observation value.
- 2) The second way to submit precision data is to refer to existing daily raw data values in the database. To submit data this way, the following fields are left null: sample duration, unit, actual method, actual value, indicated method, and indicated value. The transaction identifies the primary monitor using state, county, site, parameter, and POC; and identifies the duplicate sampler using collocated POC ID, along with the same state, county, site, and parameter values as the primary monitor. In this case, the database must contain daily raw data values for both samplers for the same day. The system will populate the precision data using those raw data values for that day.

See the data input transaction formats in the Appendices for a list of required fields on each transaction format.

7.2.1 Transaction Type

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid transaction type in the first delimited field.

7.2.2 Action Code

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new row into the appropriate table in the database.

U - Change one or more column values for an existing row in one or more

tables.

D - Delete a row from a table(s) for the row containing the key data.

7.2.3 State Code

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

DC, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

7.2.4 County Code

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

7.2.5 Site ID

Description:

A numeric identifier (ID) that uniquely identifies each air monitoring site within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID
Mandatory

Coding Instructions: Place a four-digit numeric code in the fifth delimited field. For update and

delete, a site ID value is valid if it exists in combination with state code and

county code in the Sites Table.

7.2.6 Parameter

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

7.2.7 POC (Parameter Occurrence Code)

Description:

An identifier used to distinguish between multiple monitors at the same site that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a different POC.

Attributes:

Numeric 2-digit ID Mandatory

Coding Instructions:

Place a valid POC value in the seventh delimited field. A POC value is valid

if it is between 1 and 99.

7.2.8 Precision ID

Description:

A sequentially assigned number used to identify (ID) a particular precision check from others, when multiple checks are performed on the same day.

Attributes:

Numeric

2-digit ID (nn)

Optional when using the old transaction format (80 columns) Mandatory when using the new transaction format (pipe-delimited)

Coding Instructions:

Place a valid precision ID number in the eighth delimited field. A precision ID value is valid if it is greater than 0.

For the old transaction format (80 columns): This ID is mandatory in the database, but not mandatory on the transaction. If left blank on the transaction, the system will generate a "1" for the field as part of the load step. If precision data for the same monitor on the same date already exists (in the database or in the transaction set), the system will not increment the number being generated for the field. A "1"will still be system-generated for each blank precision ID field on

the transactions.

Therefore, if an agency is attempting to submit multiple precision transactions for the same day and monitor, and is leaving this field blank, then all of the RP transactions in the job will get a system-generated "1" in this field. Then the transactions for the same day and monitor will reject because they are not unique (they will all have a precision ID of "1").

So be sure to manually supply unique values for this field if you are submitting more than one set of precision data values for the same day and monitor.

The above applies to the old transaction format only.

For the new transaction format (pipe-delimited), the precision ID must be supplied.

7.2.9 Sample Duration

Description: The period of time during which the raw sample value was collected.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place a valid sample duration code in the ninth delimited field. A sample

duration value is valid if it exists in the Sample Durations Table and if it exists in combination with unit, parameter, method, and collection frequency

in the Protocols Table.

7.2.10 Unit

Description: The dimensional system in which the pollutant concentration or parameter

reading is expressed.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid unit code in the tenth delimited field. A unit value is valid if it

exists in the Units Table, and if it exists in combination with parameter, sampling duration, method, and collection frequency in the Protocols Table.

7.2.11 Actual Method

Description: Identifies the particular method for collecting and analyzing the indicated

precision check value. For a collocated data pair, this represents the method used to collect and analyze the sample value from the primary sampler.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid method code in the eleventh delimited field.

For a precision check that is not a collocated data pair, an actual method value is valid if it exists in combination with parameter in the Sampling Methodologies Table, and if it exists in combination with sample duration,

unit, and collection frequency in the Protocols Table.

For a collocated data pair, it is valid if it matches the method associated with the daily raw data point collected by the primary sampler on the precision

date.

7.2.12 Date

Description: The calendar date for which the precision check is being reported.

Attributes: Date

8-digit date Mandatory

Coding Instructions: Place a valid date in the twelfth delimited field. A date value is valid if:

It is in the form of YYYYMMDD,

It is between January 1, 1980 and the current date,

It falls within a valid sample period defined for the monitor, and, If a criteria pollutant monitor is being audited, it falls within a valid

reporting organization period.

7.2.13 Actual Value

Description: The true value of the parameter concentration with which the monitor was

challenged. For a collocated data pair, the sample value from the primary

sampler.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Mandatory (Not required if value is stored as raw data. If reported, it must

equal the value in the Raw Data Table)

Coding Instructions: Place the true value in the thirteenth delimited field.

For some parameters, upper limits have been established for precision observations, and the numeric value entered cannot exceed that maximum.

The relevant maximum values and parameters are listed below:

Parameter Code	Parameter Description	Maximum Precision Value
11101	Suspended Particulate (TSP)	2000 μg/m³ (25 c)
12128	Lead (TSP)	80 μg/m³ (25 c)
42101	Carbon Monoxide	20 ppm
42401	Sulfur Dioxide	0.2 ppm
42602	Nitrogen Dioxide	0.2 ppm
44201	Ozone	0.2 ppm
81102	PM-10 Total 0 - 10 um	2000 μg/m³ (25 c)
88101	PM-2.5 Local Conditions	2000 μg/m³ (LC)

For some parameters, percent differences are utilized to reject data that could be in error as a result of transcription errors. The maximum percent differences and parameters are listed below:

Parameter Code	Parameter Description	Maximum Percent Difference
11101	Suspended Particulate (TSP)	<u>+</u> 160 %
12128	Lead (TSP)	<u>+</u> 160 %
42101	Carbon Monoxide	<u>+</u> 90 %
42401	Sulfur Dioxide	<u>+</u> 90 %
42602	Nitrogen Dioxide	<u>+</u> 90 %
44201	Ozone	<u>+</u> 90 %
81102	PM-10 Total 0 - 10 um	<u>+</u> 160 %
88101	PM-2.5 Local Conditions	<u>+</u> 160 %

For 11101, 12128, and 81102, the percent difference is calculated using the following formula:

$$\frac{2(indicated - actual)}{(indicated + actual)}$$
 × 100

For 42101, 42401, 42602, and 44201, the percent difference is calculated using the following formula:

7.2.14 Indicated Method

Description: Identifies the particular method for collecting and analyzing the sample value

from the duplicate sampler. Only applies to collocated data.

Attributes: Alphanumeric

3-digit code Optional

Coding Instructions: Place a valid method code in the fourteenth delimited field. An indicated

method value is valid if it matches the method associated with the daily raw data point collected by the duplicate sampler on the precision date. (The duplicate sampler is identified by state code, county code, site ID, parameter,

and collocated POC.)

7.2.15 Indicated Value

Description: The observed value of the parameter concentration with which the monitor

was challenged. For a collocated data pair, the sample value from the

duplicate sampler.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Mandatory

Coding Instructions: Place the indicated value in the fifteenth delimited field. An indicated value

is valid if its percentage difference relative to the test value does not exceed

the level defined for the parameter on the Parameters Table.

For some parameters, upper limits have been established for precision observations, and the numeric value entered cannot exceed that maximum. The relevant maximum values and parameters are listed below:

Parameter Code Parameter Description Maximum Precision Value Suspended Particulate (TSP) 11101 2000 µg/m³ (25 c) Lead (TSP) $80 \mu g/m^3 (25 c)$ 12128 42101 Carbon Monoxide 20 ppm 42401 Sulfur Dioxide 0.2 ppm 42602 Nitrogen Dioxide 0.2 ppm 44201 Ozone 0.2 ppm 2000 µg/m³ (25 c) 81102 PM-10 Total 0 - 10 um 88101 PM-2.5 Local Conditions 2000 μg/m³ (LC)

For some parameters, percent differences are utilized to reject data that could be in error as a result of transcription errors. The maximum percent differences and parameters are listed below:

Parameter Code	Parameter Description	Maximum Percent Difference
11101	Suspended Particulate (TSP)	<u>+</u> 160 %
12128	Lead (TSP)	<u>+</u> 160 %
42101	Carbon Monoxide	<u>+</u> 90 %
42401	Sulfur Dioxide	<u>+</u> 90 %
42602	Nitrogen Dioxide	<u>+</u> 90 %
44201	Ozone	<u>+</u> 90 %
81102	PM-10 Total 0 - 10 um	<u>+</u> 160 %
88101	PM-2.5 Local Conditions	<u>+</u> 160 %

For 11101, 12128, and 81102, the percent difference is calculated using the following formula:

$$\frac{2(indicated - actual)}{(indicated + actual)} \times 100$$

For 42101, 42401, 42602, and 44201, the percent difference is calculated using the following formula:

7.2.16 Collocated POC ID

Description: The POC of the duplicate sampler. Only applies to collocated data where the

duplicate value is a recorded daily raw data point.

Attributes: Numeric

2-digit ID Optional

Coding Instructions: Place a valid collocated POC ID in the sixteenth delimited field. A

collocated POC is valid if it exists in combination with state code, county code, site ID, and parameter on the Monitors Table, and if there is a sample

value recorded for that monitor in raw data on the precision date.

7.2.17 Precision Sample ID

Description: The unique identity (ID) number of the reference sample used to challenge

the instrument.

Attributes: Alphanumeric

10 characters Optional

Coding Instructions: Place the precision check sample ID alphanumeric text in the seventeenth

delimited field. No edit checks are performed on an precision sample ID

value.

7.2.18 Agency Performing Audit

Description: The agency submitting precision data resulting from a Federal Reference

Method (FRM) audit of the manual method for PM-2.5 monitoring. This

agency is commonly an EPA laboratory or independent laboratory.

Do not use this field to identify the air pollution control agency that is responsible for the monitor, its data, and routine precision and accuracy data, because precision data submitted on this transaction (RP) with this field (agency performing audit) populated will not be included in the summary

statistical data for the monitor.

Attributes: Alphanumeric

4-digit code Optional

Coding Instructions: Place a valid agency performing audit code in the eighteenth delimited field.

An agency performing audit value is valid if it exists in combination with

state code in the State Agencies Table.

This transaction will be rejected if the precision audit is not an FRM audit.

The actual value must be blank and must have been reported by the reporting

agency as raw data.

8.0 ANNUAL SUMMARY DATA - TRANSACTION TYPE RS

Annual summary data is usually system-generated from the raw data contained in the system. However, the new AQS makes provision for storing summary data from agencies when they will not be submitting raw data.

Transaction type RS contains annual summary data in the following fields:

Transaction Type Time of 2nd Highest Sample Value

Action Code
State Code
State Code
County Code
Site ID
State Code
Ath Highest Sample Value
Sth Highest Sample Value
Lowest Sample Value
Arithmetic Mean

POC Arithmetic Standard Deviation

Sample Duration Geometric Mean

Unit Geometric Standard Deviation

Method 10th Percentile 25th Percentile Year 50th Percentile Exceptional Data Type Count of Observations 75th Percentile 90th Percentile Number of Exceptional Events Highest Sample Value 95th Percentile Date of Highest Sample Value 98th Percentile Time of Highest Sample Value 99th Percentile

2nd Highest Sample Value Percent of Observations

Date of 2nd Highest Sample Value Number < MDL

8.1 TRANSACTION TYPE

Description: Specifies which batch transaction is being processed by the batch load

software (i.e., which tables and columns will be updated with the data in the

delimited fields).

Attributes: Alphanumeric

2-character code

Mandatory

Coding instructions: Place the text RS in the first delimited field.

8.2 ACTION CODE

Description: Indicates the data manipulation action to be performed by the transaction.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place the values I, U, or D in the second delimited field.

I - Insert a new summary row into the Annual Summaries Table and associated rows in the Summary Maximums, Summary Percentiles, and Summary Protocols Tables.

U - Change one or more columns within related annual summaries, summary maximums, summary percentiles, and summary protocols rows.

D - Delete an annual summary row from the Annual Summaries Table and associated rows in the Summary Maximums, Summary Percentiles, and Summary Protocols Tables.

8.3 STATE CODE

Description: A FIPS code that identifies one of the 50 states, U. S. territories, Washington,

D.C, or foreign countries.

Attributes: Alphanumeric

2-character code

Mandatory

Coding Instructions: Place a valid FIPS state code in delimited field 3. A code is valid if it exists

in the States Table.

8.4 COUNTY CODE

Description: A FIPS code that identifies a county, or equivalent geo-political entity, such

as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian

provinces.

Attributes: Alphanumeric

3-character code

Mandatory

Coding Instructions: Place a valid county code in the fourth delimited field. A code is valid if it

exists in combination with state code and city code, in the County Cities

Table.

8.5 SITE ID

Description: A numeric identifier (ID) that uniquely identifies each air monitoring site

within a county. There is no requirement that site IDs be assigned continuously or in any particular order. Local organizations are thus free to allocate site numbers in any way they chose as long as there is no duplication

within a county.

A specific site ID is associated with a specific physical location and address. Any change in address requires a new site ID to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new site ID. Although an address change would routinely mean a new site ID, some changes that do not change the site's location in respect to surrounding sources and its measurement scale, would require no change. An EPA Regional Office should be consulted for assistance in determining whether a new site ID is required.

If a new site ID is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new site ID is assigned, it must be different from any other site ID already existing for that combination of state ID and county code.

Attributes: Alphanumeric

4-digit ID Mandatory

Coding Instructions: Place a four-digit side ID in the fifth delimited field. A site ID value is valid

if it exists in combination with state code and county code in the Sites Table.

8.6 PARAMETER

Description: The code assigned to the parameter measured by the monitor. Parameters

may be pollutants or non-pollutants.

Attributes: Alphanumeric

5-digit code Mandatory

Coding Instructions: Place a valid parameter code in the sixth delimited field. A parameter value

is valid if it exists in combination with state code, county code, site ID, and

POC in the Monitors Table.

8.7 POC (Parameter Occurrence Code)

Description: An identifier used to distinguish between multiple monitors at the same site

that are measuring the same parameter. For example, the first monitor established to measure CO at a site could have a POC of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a POC of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor

and it would still have a POC of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same POC if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple samplers, multiple POCs must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same POC if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a different POC.

Attributes: Numeric

2-digit ID Mandatory

Coding Instructions: Place a valid POC value in the seventh delimited field. A POC value is valid

if it exists in combination with state code, county code, site ID, and parameter

on the Monitors Table.

8.8 SAMPLE DURATION

Description: The period of time during which all the raw data sample values being

summarized were collected.

Attributes: Alphanumeric

1-character code

Mandatory

Coding Instructions: Place a valid sample duration code in the eighth delimited field. A sample

duration value is valid if it exists in the Sample Durations Table and if it exists in combination with unit, parameter, and method in the Protocols

Table.

8.9 UNIT

Description: The dimensional system in which the summary values are expressed.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid unit code in the ninth delimited field. A unit value is valid if it

exists in the Units Table and if it exists in combination with sample duration,

parameter, and method in the Protocols Table.

8.10 METHOD

Description: Identifies the particular method for collecting and analyzing the raw data

values that are the basis of the summary values.

Attributes: Alphanumeric

3-digit code Mandatory

Coding Instructions: Place a valid method code in the tenth delimited field. A method value is

valid if it exists in combination with parameter in the Sampling Methodologies Table, and if it exists in combination with sample duration,

unit, and collection frequency in the Protocols Table.

8.11 YEAR

Description: The year whose raw data is summarized.

Attributes: Date

4-digit year (yyyy)

Mandatory

Coding Instructions: Place a valid year number in the eleventh delimited field. A year value is

valid if it is in the format of YYYY and there is a valid sampling period

defined for the monitor in that year.

8.12 EXCEPTIONAL DATA TYPE

Description: Indication of whether exceptional data exists in the year being summarized,

and whether such exceptional data is included in the reported summary

values.

Attributes: Numeric

1-digit code (n) Mandatory

Coding Instructions: Place a valid exceptional data type number in the twelfth delimited field. An

exceptional data type value is valid if it exists in the Exceptional Data Types

Table.

8.13 COUNT OF OBSERVATIONS

Description: The number of raw data values that are the basis for the summary values.

Attributes: Numeric

5 digits (nnnnn)

Optional

Coding Instructions: Place a valid count of observations in the thirteenth delimited field. A count

of observations value is valid if it is greater than 0.

8.14 NUMBER OF EXCEPTIONAL EVENTS

Description: The number of data points in the summarized data set that were qualified by

exceptional events.

Attributes: Numeric

5 digits (nnnnn)

Optional

Coding Instructions: Place a valid number of exceptional events value in the fourteenth delimited

field. A number of exceptional events value is valid if:

1) it is 0 and the exceptional data type is 0 or 1; or

2) it is greater than 0 and less than or equal to count of observations,

and exceptional data type is 2.

8.15 HIGHEST SAMPLE VALUE

Description: The highest sample value in the yearly sample value set.

Attributes: Numeric

10 digits, including 5 decimal places (nnnn.nnnnn)

Optional

Coding Instructions: Place a valid highest sample value in the fifteenth delimited field. A highest

sample value is valid if it is greater than or equal to the second, third, fourth,

and fifth highest values reported on the transaction record.

8.16 DATE OF HIGHEST SAMPLE VALUE

Description: The earliest date on which the highest sample value in the yearly data set was

reported.

Attributes: Date

8-digit date Optional

Coding Instructions: Place a valid date of highest sample value in the sixteenth delimited field. A

date of highest sample value is valid if it is in the format of YYYYMMDD

where the year portion is equal to year.

8.17 TIME OF HIGHEST SAMPLE VALUE

Description: The time of day at which the highest sample value in the yearly data set was

reported.

Attributes: Alphanumeric

5 characters Optional

Coding Instructions: Place a valid time of highest sample value in the seventeenth delimited field.

A time of highest sample value is valid if it is in the form of HH:MM, where

HH is between 00 and 23, and MM is between 00 and 59.

8.18 SECOND HIGHEST SAMPLE VALUE

Description: The second highest sample value in the yearly sample value set.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place a sample second highest sample value in the eighteenth delimited field.

A second highest sample value is valid if it is not greater than highest sample value, and is greater than or equal to the third, fourth, and fifth highest values

reported on the transaction record.

8.19 DATE OF SECOND HIGHEST SAMPLE VALUE

Description: If the second highest value is less than the highest, this identifies the earliest

date on which the second highest sample value in the yearly data set was reported; if the second highest is equal to the highest, this identifies the

second earliest date on which the value was reported.

Attributes: Date

8-digit date Optional

Coding Instructions: Place a valid date of second highest sample value in the nineteenth delimited

field. A date of second highest sample value is valid if it is in the format of YYYYMMDD where the year portion is equal to year. If the highest sample value and second highest sample value are equal, then date of second highest

sample must be greater than date of highest sample value.

8.20 TIME OF SECOND HIGHEST SAMPLE VALUE

Description: The time of day on which the second highest sample value in the yearly data

set was reported.

Attributes: Alphanumeric

5 characters Optional

Coding Instructions: Place a valid time of highest sample value in the twentieth delimited field.

A time of highest sample value is valid if it is in the form of HH:MM, where

HH is between 00 and 23, and MM is between 00 and 59.

8.21 THIRD HIGHEST SAMPLE VALUE

Description: The third highest sample value in the yearly sample value set.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place a third highest sample value in the twenty-first delimited field. A third

highest sample value is valid if it is not greater than second highest sample value, and is greater than or equal to the fourth and fifth highest values

reported on the transaction record.

8.22 FOURTH HIGHEST SAMPLE VALUE

Description: The fourth highest sample value in the yearly sample value set.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place a fourth highest sample value in the twenty-second delimited field. A

fourth highest sample value is valid if it is not greater than third highest sample value, and is greater than or equal to the fifth highest value reported

on the transaction record.

8.23 FIFTH HIGHEST SAMPLE VALUE

Description: The fifth highest sample value in the yearly sample value set.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place a fifth highest sample value in the twenty-third delimited field. A fifth

highest sample value is valid if it is not greater than fourth highest sample

value.

8.24 LOWEST SAMPLE VALUE

Description: The lowest sample value in the yearly sample value set.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place a lowest sample value in the twenty-fourth delimited field. A lowest

sample value is valid if it is not greater than the lowest of the highest values

reported on the transaction record.

8.25 ARITHMETIC MEAN

Description: The measure of central tendency obtained from the sum of the observed

pollutant data values in the yearly data set divided by the number of values

that comprise the sum for the yearly data set.

Attributes: Numeric

10 digits, including 5 decimal places (nnnn.nnnnn)

Optional

Coding Instructions: Place the arithmetic mean in the twenty-fifth delimited field.

8.26 ARITHMETIC STANDARD DEVIATION

Description: The measure of the dispersion about the central tendency of a pollutant that

is the square root of the arithmetic mean of the squares of the variation of each data value from the arithmetic mean of the data values of the yearly data

set.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place the arithmetic standard deviation in the twenty-sixth delimited field.

8.27 GEOMETRIC MEAN

Description: The measure of central tendency obtained from the sum of the logarithms of

observed sample values in the yearly data set, divided by the number of

values, with that result applied as an exponent to 10.

Attributes: Numeric

10 digits, including 5 decimal places (nnnn.nnnn)

Optional

Coding Instructions: Place the geometric mean in the twenty-seventh delimited field.

8.28 GEOMETRIC STANDARD DEVIATION

Description: The measure of the dispersion about the central tendency of a pollutant that

is based on the variation between the geometric mean of a sample of values

and the logarithms of the values themselves.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place the geometric standard deviation in the twenty-eighth delimited field.

8.29 10TH PERCENTILE

Description: The sample value occurring in the tenth percentile of the yearly data set when

sorted from lowest to highest.

Attributes: Numeric

10 digits, including 5 decimal places (nnnn.nnnn)

Optional

Coding Instructions: Place the sample value in the twenty-ninth delimited field.

8.30 25TH PERCENTILE

Description: The sample value occurring in the twenty-fifth percentile of the yearly data

set when sorted from lowest to highest.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place the sample value in the thirtieth delimited field.

8.31 50TH PERCENTILE

Description: The sample value occurring in the fiftieth percentile of the yearly data set

when sorted from lowest to highest.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place the sample value in the thirty-first delimited field.

8.32 75TH PERCENTILE

Description: The sample value occurring in the seventy-fifth percentile of the yearly data

set when sorted from lowest to highest.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place the sample value in the thirty-second delimited field.

8.33 90TH PERCENTILE

Description: The sample value occurring in the ninetieth percentile of the yearly data set

when sorted from lowest to highest.

Attributes: Numeric

10 digits, including 5 decimal places (nnnn.nnnnn)

Optional

Coding Instructions: Place the sample value in the thirty-third delimited field.

8.34 95TH PERCENTILE

Description: The sample value occurring in the ninety-fifth percentile of the yearly data set

when sorted from lowest to highest.

Attributes: Numeric

10 digits, including 5 decimal places (nnnn.nnnnn)

Optional

Coding Instructions: Place the sample value in the thirty-fourth delimited field.

8.35 98TH PERCENTILE

Description: The sample value occurring in the ninety-eighth percentile of the yearly data

set when sorted from lowest to highest.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place the sample value in the thirty-fifth delimited field.

8.36 99TH PERCENTILE

Description: The sample value occurring in the ninety-ninth percentile of the yearly data

set when sorted from lowest to highest.

Attributes: Numeric

10 digits, including 5 decimal places (nnnnn.nnnnn)

Optional

Coding Instructions: Place the sample value in the thirty-sixth delimited field.

8.37 PERCENT OF OBSERVATIONS

Description: The percent of actual data values that were reported compared to the number

of data values that could have been reported for the year.

Attributes: Numeric

10 digits, including 4 decimal places (nnnnn.nnnn)

Optional

Coding Instructions: Place the observation percentage in the thirty-seventh delimited field.

8.38 NUMBER LESS THAN MINIMUM DETECTABLE VALUE

Description: Represents the number of substitutions of one-half the Method Detectable

Limit value for the year.

Attributes: Numeric

5 digits (nnnnn)

Optional

Coding Instructions: Place the count of observations with one-half the MDL in the thirty-eighth

delimited field.